

External wall - awroho01b-04

external wall, timber frame construction, not ventilated, without dry lining, with cladding, other surface

Performance rating

| | | |
|------------------------------------------------------------------------------------------------|------------------|----|
| Fire protection performance | REI from inside | 60 |
| | REI from outside | 30 |
| maximum ceiling height = 3 m; maximum load $E_{d,fi} = 32,0 \text{ kN/m}$ Classified by HFA | | |

| | | |
|----------------------------|-----------|--------------------------------------|
| Thermal performance | U | 0.19 $\text{W}/(\text{m}^2\text{K})$ |
| | Diffusion | suitable |


Calculated by HFA

| | | |
|-----------------------------|-------------------|--------------|
| Acoustic performance | $R_w (C; C_{tr})$ | 52(-1;-6) dB |
| | $L_{n,w} (C_i)$ | |

Assessed by MA39

| | | |
|---------------------------|---|------------------------------|
| Mass per unit area | m | 80.70 kg/m^2 |
|---------------------------|---|------------------------------|

Calculation based on GF



Note: e=625

Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

| | Thickness | Building material | Thermal performance | | | | Reaction to fire EN |
|---|-----------|-----------------------------------|---------------------|-----------------|--------|-------|---------------------|
| | | | λ | μ min - max | ρ | c | |
| A | 24.0 | larch wood external wall cladding | 0.155 | 150 | 600 | 1.600 | D |
| B | 24.0 | spruce wood cross battens | 0.120 | 50 | 450 | 1.600 | D |
| C | 50.0 | wood wool composite boards | 0.090 | 2 - 5 | 370 | 2.000 | B |
| D | 15.0 | fibreboard (MDF) | 0.140 | 11 | 600 | 1.700 | D |
| E | 160.0 | construction timber (60/..; e=*) | 0.120 | 50 | 450 | 1.600 | D |
| F | 160.0 | mineral wool [035; 50; <1000°C] | 0.035 | 1 | 50 | 1.030 | A1 |
| G | 15.0 | OSB (sealed with airtight tape) | 0.130 | 200 | 600 | 1.700 | D |
| H | 15.0 | gypsum fibre board or | 0.320 | 21 | 1000 | 1.100 | A2 |
| H | 15.0 | gypsum plaster board type DF | 0.250 | 10 | 800 | 1.050 | A2 |

Sustainability rating (per m^2)

Database ecoinvent

$O13_{kon}$ 43.8

Calculated by HFA

Details of sustainability rating

Database ecoinvent

| Lifecycle (Phases) | GWP [kg CO ₂ -e.] | AP [kg SO ₂ -e.] | EP [kg PO ₄ -e.] | ODP [kg R11-e.] | POCP [kg Ethen-e.] | |
|-----------------------|---------------------------------|--------------------------------|--------------------------------|--------------------|-----------------------|--|
| A1 - A3 | | 0.197 | 0.086 | 3,54E-6 | 0.032 | |

| Lifecycle (Phases) | PERE [MJ] | PERM [MJ] | PERT [MJ] | PENRE [MJ] | PENRM [MJ] | PENRT [MJ] |
|-----------------------|--------------|--------------|--------------|---------------|---------------|---------------|
| A1 - A3 | 133.687 | 752.424 | 886.111 | 661.403 | 28.891 | 690.294 |