

Designation: awropi04b-13 Last updated: 8/2/23

Holzforschung Austria Source:

Editor: HFA, SP

# External wall - awropi04b-13

external wall, timber frame construction, not ventilated, with dry lining, with rendering, other surface

## Performance rating


**REI** from inside 60 Fire protection performance REI from outside 90 maximum ceiling height = 3 m; maximum load  $E_{d,fi}$  = 32,0 kN/m Classified by HFA

Thermal performance	U Diffusion	0.15 W/(m <sup>2</sup> K) suitable
Calculated by HFA		
Acoustic performance	$R_w$ (C;C <sub>tr</sub> ) $L_{n,w}$ (C <sub>I</sub> )	53(-2;-9) dB

Rw(C;Ctr)=51(-1;-7) dB Assessed by MA39

Mass per unit area  $71.00 \text{ kg/m}^2$ 

Calculation based on gypsum plaster board type DF



Note: e=625

#### Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

	Thickness	Building material	Thermal pe	rformance			Reaction to fire
			λ	μ min – max	ρ	С	EN
Α	7.0	plaster	1.000	10 - 35	2000	1.130	A1
В	100.0	wood-fibre insulation board WF-PT [045; 180]	0.045	5 - 7	180	2.100	E
С	160.0	construction timber (60/; e=*)	0.120	50	450	1.600	D
D	160.0	mineral wool [040; ≥16; <1000°C]	0.040	1	16	1.030	A1
E	18.0	OSB (sealed with airtight tape)	0.130	200	600	1.700	D
F	40.0	spruce wood cross battens (a=400) or battens offset)	0.120	50	450	1.600	D
G	40.0	mineral wool [040; ≥16; <1000°C] or air layer in type 02	0.040	1	16	1.030	A1
Н	15.0	gypsum plaster board type DF or	0.250	10	800	1.050	A2
Н	15.0	gypsum fibre board	0.320	21	1000	1.100	A2

## Sustainability rating (per m<sup>2</sup>)

Database ecoinvent

OI3<sub>Kon</sub> 46.4

Calculated by HFA



Designation: awropi04b-13 Last updated:

8/2/23 Holzforschung Austria Source:

Editor: HFA, SP

### Details of sustainability rating

#### Database ecoinvent

	1					
Lifecycle	GWP	AP	EP	ODP	POCP	
(Phases)	[kg CO <sub>2</sub> -e.]	[kg SO <sub>2</sub> -e.]	[kg PO <sub>4</sub> -e.]	[kg R11-e.]	[kg Ethen-e.]	
A1 - A3		0.196	0.088	3,90E-6	0.029	
	,					·
Lifecycle	PERE	PERM	PERT	PENRE	PENRM	PENRT
(Phases)	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]
A1 - A3	122.007	752.554	874.561	707.435	52.273	759.707