

Designation: awropi14a-04 8/2/23 Last updated:

Holzforschung Austria Source:

Editor: HFA, SP

# External wall - awropi14a-04

external wall, timber frame construction, not ventilated, with dry lining, with rendering, other surface

### Performance rating


**REI** from inside 60 Fire protection performance RFI from outside 60 maximum ceiling height = 3 m; maximum load  $E_{d,fi}$  = 32,0 kN/m Classified by HFA

Thermal performance	U Diffusion	0.13 W/(m <sup>2</sup> K) suitable
Calculated by HFA		
Acoustic performance	R <sub>w</sub> (C;C <sub>tr</sub> ) L <sub>n,w</sub> (C <sub>l</sub> )	54(-3;-10) dB
Vertical hattens for the dr	v lining screwed onto	the ledger heams lead to an

Rw(C;Ctr)=51(-1;-7) dB

Assessed by MA39

Mass per unit area Calculation based on gypsum plaster board type DF



Note: e=625

### Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

 $77.10 \text{ kg/m}^2$ 

	Thickness	Building material	Thermal per	rformance			Reaction to fire
			λ	μ min – max	ρ	С	EN
4	7.0	plaster	1.000	10 - 35	2000	1.130	A1
3	60.0	wood-fibre insulation board WF-PT [045; 180]	0.045	5 - 7	180	2.100	E
2	10.0	gypsum fibre board	0.320	21	1000	1.100	A2
D	240.0	construction timber (60/; e=*)	0.120	50	450	1.600	D
E	240.0	mineral wool [040; ≥16; <1000°C]	0.040	1	16	1.030	A1
F	12.5	gypsum fibre board	0.320	21	1000	1.100	A2
G		vapour barrier sd≥ 3 m			1000		
Н	40.0	spruce wood cross battens (a=400) or battens offset)	0.120	50	450	1.600	D
	40.0	mineral wool [040; ≥16; <1000°C]	0.040	1	16	1.030	A1
	12.5	gypsum plaster board type DF or	0.250	10	800	1.050	A2
	12.5	gypsum fibre board	0.320	21	1000	1.100	A2

## Sustainability rating (per m²)

Database ecoinvent  $013_{Kon}$ 44.0

Calculated by HFA



Designation: awropi14a-04 8/2/23 Holzforschung Austria Last updated:

Source:

Editor: HFA, SP

## Details of sustainability rating

### Database ecoinvent

Lifecycle	GWP	AP	EP	ODP	POCP	
(Phases)	[kg CO <sub>2</sub> -e.]	[kg SO <sub>2</sub> -e.]	[kg PO <sub>4</sub> -e.]	[kg R11-e.]	[kg Ethen-e.]	
A1 - A3		0.174	0.078	3,71E-6	0.025	
Lifecycle	PERE	PERM	PERT	PENRE	PENRM	PENRT
(Phases)	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]
A1 - A3	87.498	475.626	563.124	641.226	30.052	671.278