

Designation: awropi15a-06 8/2/23 Last updated:

Holzforschung Austria Source:

Editor: HFA, SP

External wall - awropi15a-06

external wall, timber frame construction, not ventilated, with dry lining, with rendering, other surface

Performance rating


REI from inside 60 Fire protection performance RFI from outside 60 maximum ceiling height = 3 m; maximum load $E_{d,fi}$ = 32,0 kN/m Classified by HFA

Thermal performance Calculated by HFA	U Diffusion	0.12 W/(m ² K) suitable
Acoustic performance	R _w (C;C _{tr}) L _{n,w} (C _I)	54(-3;-10) dB

Vertical battens for the dry lining screwed onto the ledger beams lead to an Rw(C;Ctr)=51(-1;-7) dB Assessed by MA39

Mass per unit area 79.80 kg/m^2

Calculation based on gypsum plaster board type DF



Note: e=625

Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

	Thickness	Building material	Thermal per	rformance			Reaction to fire
			λ	μ min – max	ρ	С	EN
A	7.0	plaster	1.000	10 - 35	2000	1.130	A1
В	60.0	wood-fibre insulation board WF-PT [045; 180]	0.045	5 - 7	180	2.100	E
С	12.0	particleboard P5	0.130	50 - 100	700	1.700	D
D	240.0	construction timber (60/; e=*)	0.120	50	450	1.600	D
E	240.0	mineral wool [040; ≥16; <1000°C]	0.040	1	16	1.030	A1
=	16.0	particleboard P4	0.130	50 - 100	700	1.700	D
Ĵ		vapour barrier sd≥ 7m			1000		
1	80.0	spruce wood cross battens (a=400) or battens offset)	0.120	50	450	1.600	D
	80.0	mineral wool [040; ≥16; <1000°C]	0.040	1	16	1.030	A1
	12.5	gypsum plaster board type DF or	0.250	10	800	1.050	A2
J	12.5	gypsum fibre board	0.320	21	1000	1.100	A2

Sustainability rating (per m²)

Database ecoinvent 013_{Kon} 50.9 Calculated by HFA



Designation: awropi15a-06 8/2/23 Holzforschung Austria Last updated:

Source:

HFA, SP Editor:

Details of sustainability rating

Database ecoinvent

Lifecycle	GWP	AP	EP	ODP	POCP	
(Phases)	[kg CO ₂ -e.]	[kg SO ₂ -e.]	[kg PO ₄ -e.]	[kg R11-e.]	[kg Ethen-e.]	
A1 - A3		0.210	0.094	3,88E-6	0.036	
Lifecycle	PERE	PERM	PERT	PENRE	PENRM	PENRT
(Phases)	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]