

External wall - awropi20a-03

external wall, timber frame construction, not ventilated, with dry lining, with rendering, other surface

Performance rating

Fire protection performance
 REI from inside 60
 REI from outside 60
 maximum ceiling height = 3 m; maximum load $E_{d,fi} = 32,0 \text{ kN/m}$
 Classified by HFA

Thermal performance
 U 0.15 $\text{W}/(\text{m}^2\text{K})$
 Diffusion suitable


Calculated by HFA

Acoustic performance
 $R_w (C; C_{tr})$ 53(-3;-11) dB
 $L_{n,w} (C_i)$

vertical battens for the dry lining screwed onto the structural timber lead to an $R_w(C; C_{tr})=51(-2;-8)$ dB
 Assessed by MA39

Mass per unit area m 68.10 kg/m^2

Calculation based on gypsum plaster board type DF



Note: e=625

Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

| | Thickness | Building material | Thermal performance | | | | Reaction to fire EN |
|---|-----------|---|---------------------|--------------------------------|--------|-------|------------------------|
| | | | λ | $\mu \text{ min} - \text{max}$ | ρ | c | |
| A | 7.0 | plaster | 1.000 | 10 - 35 | 2000 | 1.130 | A1 |
| B | 60.0 | wood-fibre insulation board WF-PT [045; 180] | 0.045 | 5 - 7 | 180 | 2.100 | E |
| C | 200.0 | construction timber (60/-; e=*) | 0.120 | 50 | 450 | 1.600 | D |
| D | 200.0 | mineral wool [040; ≥ 16 ; $< 1000^\circ\text{C}$] | 0.040 | 1 | 16 | 1.030 | A1 |
| E | 19.0 | particleboard | 0.130 | 50 - 100 | 700 | 1.700 | D |
| F | | vapour barrier sd $\geq 2\text{m}$ | | | 1000 | | |
| G | 40.0 | spruce wood cross battens (a=400) or battens offset | 0.120 | 50 | 450 | 1.600 | D |
| H | 40.0 | mineral wool [040; ≥ 16 ; $< 1000^\circ\text{C}$] or air layer in type 02 | 0.040 | 1 | 16 | 1.030 | A1 |
| I | 12.5 | gypsum plaster board type DF or | 0.250 | 10 | 800 | 1.050 | A2 |
| I | 12.5 | gypsum fibre board | 0.320 | 21 | 1000 | 1.100 | A2 |

Sustainability rating (per m^2)

Database ecoinvent

013_{Kon} 42.8

Calculated by HFA

Details of sustainability rating

Database ecoinvent

| Lifecycle (Phases) | GWP [kg CO ₂ -e.] | AP [kg SO ₂ -e.] | EP [kg PO ₄ -e.] | ODP [kg R11-e.] | POCP [kg Ethen-e.] | |
|-----------------------|---------------------------------|--------------------------------|--------------------------------|--------------------|-----------------------|--|
| A1 - A3 | | 0.175 | 0.078 | 3.32E-6 | 0.029 | |

| Lifecycle (Phases) | PERE [MJ] | PERM [MJ] | PERT [MJ] | PENRE [MJ] | PENRM [MJ] | PENRT [MJ] |
|-----------------------|--------------|--------------|--------------|---------------|---------------|---------------|
| A1 - A3 | 81.698 | 638.178 | 719.876 | 651.435 | 57.446 | 708.881 |