

### External wall - awropi31a-02

external wall, timber frame construction, not ventilated, with dry lining, with rendering, other surface


#### Performance rating

**Fire protection performance** REI from inside 60  
 REI from outside 90  
 maximum ceiling height = 3 m; maximum load  $E_{d,fi} = 32,0 \text{ kN/m}$   
 Classified by HFA

**Thermal performance** U 0.12  $\text{W}/(\text{m}^2\text{K})$   
 Diffusion suitable  
 Calculated by HFA

**Acoustic performance**  $R_w (C;C_{tr})$  46(-2;-8) dB  
 $L_{n,w} (C_i)$   
 frequency range 50-3500:  $C_{50-3500} -8 \text{ dB}$ ;  $C_{tr} 50-3500 -19 \text{ dB}$   
 Assessed by HFA

**Mass per unit area** m 76.60  $\text{kg}/\text{m}^2$



#### Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

	Thickness	Building material	Thermal performance				Reaction to fire EN
			$\lambda$	$\mu$ min - max	$\rho$	c	
A	7.0	plaster	1.000	10 - 35	2000	1.130	A1
B	100.0		0.040	1	100	1.030	A1
C	15.0	OSB	0.130	200	600	1.700	D
D	200.0	construction timber (60/60; e=625)	0.120	50	450	1.600	D
E	200.0	Cellulose fibre [040; 50]	0.040	1	50	2.000	E
F	15.0	OSB	0.130	200	600	1.700	D
G		vapour barrier $s_d \geq 14\text{m}$					
H	60.0	spruce wood - cross battens (60/60) vertical (a=625)	0.120	50	450	1.600	D
I	60.0	Cellulose fibre [040; 50]	0.040	1	50	2.000	E
J	12.5	gypsum plaster board type DF or	0.250	10	800	1.050	A2
J	12.5	gypsum fibre board	0.320	21	1000	1.100	A2

#### Sustainability rating (per $\text{m}^2$ )

##### Database ecoinvent

$OI3_{kon}$  51.3

Calculated by HFA

### Details of sustainability rating

#### Database ecoinvent

Lifecycle (Phases)	GWP [kg CO <sub>2</sub> -e.]	AP [kg SO <sub>2</sub> -e.]	EP [kg PO <sub>4</sub> -e.]	ODP [kg R11-e.]	POCP [kg Ethen-e.]	
A1 - A3		0.251	0.085	2,97E-6	0.074	

Lifecycle (Phases)	PERE [MJ]	PERM [MJ]	PERT [MJ]	PENRE [MJ]	PENRM [MJ]	PENRT [MJ]
A1 - A3	126.000	653.626	779.626	611.663	28.482	640.145