

External wall - awropi31a-06

external wall, timber frame construction, not ventilated, with dry lining, with rendering, other surface

Performance rating

Fire protection performance	REI from inside	60
	REI from outside	90
maximum ceiling height = 3 m; maximum load $E_{d,fi} = 32,0 \text{ kN/m}$ Classified by HFA		


Thermal performance	U	0.12 $\text{W}/(\text{m}^2\text{K})$
	Diffusion	suitable

Calculated by HFA

Acoustic performance	$R_w (C;C_{tr})$	61(-5;-13) dB
	$L_{n,w} (C_i)$	

frequency range 50-3500: $C_{50-3500} -13 \text{ dB}$; $C_{tr} 50-3500 -26 \text{ dB}$
 Assessed by HFA

Mass per unit area	m	69.50 kg/m^2
---------------------------	---	------------------------------



Note: I: 75 mm mineral wool, 25 mm air layer

Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

	Thickness	Building material	Thermal performance				Reaction to fire EN
			λ	$\mu \text{ min} - \text{max}$	ρ	c	
A	7.0	plaster	1.000	10 - 35	2000	1.130	A1
B	100.0		0.040	1	100	1.030	A1
C	15.0	OSB	0.130	200	600	1.700	D
D	200.0	construction timber (60/...; e=625)	0.120	50	450	1.600	D
E	200.0	mineral wool [040; 30; $\geq 1000^\circ\text{C}$]	0.040	1	30	1.030	A1
F	15.0	OSB	0.130	200	600	1.700	D
G		vapour barrier $s_d \geq 14\text{m}$					
H	100.0	CW profile freestanding					
I	75.0	mineral wool [040; 11; $< 1000^\circ\text{C}$]	0.040	1	11	1.030	A1
J	12.5	gypsum plaster board type DF or	0.250	10	800	1.050	A2
J	12.5	gypsum fibre board	0.320	21	1000	1.100	A2

Sustainability rating (per m^2)

Database ecoinvent

$OI3_{Kon}$ 66.0

Calculated by HFA

Details of sustainability rating

Database ecoinvent

Lifecycle (Phases)	GWP [kg CO ₂ -e.]	AP [kg SO ₂ -e.]	EP [kg PO ₄ -e.]	ODP [kg R11-e.]	POCP [kg Ethen-e.]	
A1 - A3		0.301	0.098	3,21E-6	0.101	

Lifecycle (Phases)	PERE [MJ]	PERM [MJ]	PERT [MJ]	PENRE [MJ]	PENRM [MJ]	PENRT [MJ]
A1 - A3	112.390	474.675	587.065	726.993	28.482	755.475