

Designation: fdrhbi01a-01 Last updated: 8/2/23

Source: Holzforschung Austria

Editor: HFA, SP

# Flat roof - fdrhbi01 a-01

flat roof, timber frame construction, ventilated, with dry lining, not suspended, other surface

# Performance rating

Fire protection

30


48(-3;-8) dB

 $\begin{array}{ccc} A coustic \ performance & & R_w \ (C; C_{tr}) \\ & & L_{n,w} \ (C_l) \end{array}$ 

Mass per unit area m  $33.90 \text{ kg/m}^2$ 

Calculation based on GF

Assessed by TGM



Note: The design of the under-roof construction and of the counterbattens have to be specified according to the roof pitch and the national requirements. J=without insulation

### Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

1	Thickness	Building material	Thermal performance				Reaction to fire
			λ	μ min – max	ρ	С	EN
A		sheet metal roofing or plastic roofing membrane			7800		A1
А		Plastic roofing membrane					E
В	24.0	spruce wood closed cladding without spacing of cladding boards	0.120	50	450	1.600	D
С	80.0	spruce wood counter battens (ventilation)	0.120	50	450	1.600	D
D		sarking membrane sd ≤ 0,3 m			1000		E
E	22.0	softboard [045; 250] - rigid underlay	0.045	5	250	2.100	E
F	200.0	construction timber (80/*; e=800)	0.120	50	450	1.600	D
G	200.0	mineral wool [040; ≥16; <1000°C]	0.040	1	16	1.030	A1
Н		vapour barrier sd≥ 2m			1000		
ı	50.0	spruce wood cross battens (50/80;a=400)	0.120	50	450	1.600	D
J		without insulation					
K	12.5	gypsum fibre board or	0.320	21	1000	1.100	A2
K	12.5	gypsum plaster board type DF	0.250	10	800	1.050	A2

# Sustainability rating (per m<sup>2</sup>)

Database ecoinvent

Ol3<sub>Kon</sub> 34.2

Calculated by HFA



Designation: fdrhbi01a-01 Last updated:

8/2/23 Holzforschung Austria Source:

Editor: HFA, SP

### Details of sustainability rating

#### Database ecoinvent

Lifecycle	GWP	AP	EP	ODP	POCP	
(Phases)	[kg CO <sub>2</sub> -e.]	[kg SO <sub>2</sub> -e.]	[kg PO <sub>4</sub> -e.]	[kg R11-e.]	[kg Ethen-e.]	
A1 - A3		0.157	0.074	2,54E-6	0.030	
Lifecycle	PERE	PERM	PERT	PENRE	PENRM	PENRT
(Phases)	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]
A1 - A3	100.521	581.542	682.063	504.460	19.383	523.843