

Designation: fdrhbi02b-05 8/2/23 Last updated:

Holzforschung Austria Source:

Editor: HFA, SP

# Flat roof - fdrhbi02b-05

REI

flat roof, timber frame construction, ventilated, with dry lining, not suspended, other surface


# Performance rating

Fire protection

performance maximum span = 5 m; maximum load  $E_{d,fi}$  = 3,66 kN/m<sup>2</sup> Classified by HFA Thermal performance U  $0.19 \text{ W/(m}^2\text{K)}$ Diffusion suitable Calculated by HFA Acoustic performance  $R_w$  (C;C<sub>tr</sub>) 48(-3;-7) dB  $L_{n,w}$  (C<sub>I</sub>) Assessed by TGM Mass per unit area

60

Calculation based on gypsum plaster board type DF



Note: The design of the under-roof construction and of the counterbattens have to be specified according to the roof pitch and the national requirements.

### Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

 $60.00~kg/m^2$ 

	Thickness	Building material	Thermal performance				Reaction to fire	
			λ	μ min – max	ρ	С	EN	
Α		Plastic roofing membrane or					Е	
Α		sheet metal roofing			7800		A1	
В	24.0	spruce wood closed cladding without spacing of cladding boards	0.120	50	450	1.600	D	
С	80.0	spruce wood counter battens (ventilation)	0.120	50	450	1.600	D	
D		sarking membrane sd ≤ 0,3 m			1000		E	
E	22.0	softboard [045; 250] - rigid underlay	0.045	5	250	2.100	E	
F	200.0	construction timber (80/*; e=800)	0.120	50	450	1.600	D	
G	200.0	cellulose fibre [040; E]	0.040	1 - 2	55	2.000	E	
Н	16.0	particleboard	0.130	50 - 100	700	1.700	D	
I		vapour barrier sd≥ 1 m			1000			
J	24.0	spruce wood cladding with spacing of cladding boards(24/100); a=400	0.120	50	450	1.600	D	
K	25.0	gypsum plaster board type DF (2x12,5 mm) or	0.250	10	800	1.050	A2	
K	25.0	gypsum fibre board (2x12,5 mm)	0.320	21	1000	1.100	A2	

### Sustainability rating (per m<sup>2</sup>)

Database ecoinvent OI3<sub>Kon</sub> 34.7 Calculated by HFA



Designation: fdrhbi02b-05 Last updated:

8/2/23 Holzforschung Austria Source:

Editor: HFA, SP

### Details of sustainability rating

#### Database ecoinvent

Lifecycle	GWP	AP	EP	ODP	POCP	
(Phases)	[kg CO <sub>2</sub> -e.]	[kg SO <sub>2</sub> -e.]	[kg PO <sub>4</sub> -e.]	[kg R11-e.]	[kg Ethen-e.]	
A1 - A3		0.164	0.075	2.63E-6	0.033	
Lifecycle	PERE	PERM	PERT	PENRE	PENRM	PENRT
(Phases)	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]