dataholz.eu


fdrhbi03b-01 8/2/23 Holzforschung Austria HFA, SP

Flat roof - fdrhbi03b-01

flat roof, timber frame construction, ventilated, with dry lining, not suspended, other surface

Performance rating

Fire protection performance	REI	60
maximum span = 5 m; ma Classified by HFA	ximum load E _{d,fi} = 3,66 kN/	∕m²
Thermal performance	U Diffusion	0.19 W∕(m ² K) suitable
Calculated by HFA		
Acoustic performance	R _w (C;C _{tr}) L _{n,w} (C _l)	48(-3;-7) dB
Assessed by TGM		
Mass per unit area	m	55.20 kg/m ²
Calculation based on gyps	um plaster board type DF	



Note: The design of the under-roof construction and of the counterbattens have to be specified according to the roof pitch and the national requirements.

Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

	Thickness	Building material	Thermal per	formance			Reaction to fire
			λ	µ min – max	ρ	с	EN
۱.		Plastic roofing membrane or					E
۱.		sheet metal roofing			7800		A1
3	24.0	spruce wood closed cladding without spacing of cladding boards	0.120	50	450	1.600	D
:	80.0	spruce wood counter battens (ventilation)	0.120	50	450	1.600	D
)		sarking membrane sd \leq 0,3m			1000		E
	15.0	OSB	0.130	200	600	1.700	D
:	220.0	construction timber (80/; e=800)	0.120	50	450	1.600	D
i i	220.0	mineral wool [040; ≥16; <1000°C]	0.040	1	16	1.030	A1
ł	15.0	OSB	0.130	200	600	1.700	D
		vapour barrier sd≥ 11m			1000		
	24.0	spruce wood cladding with spacing of cladding boards(24/100); a=400	0.120	50	450	1.600	D
(25.0	gypsum plaster board type DF (2x12,5 mm) or	0.250	10	800	1.050	A2
(25.0	gypsum fibre board (2x12,5 mm)	0.320	21	1000	1.100	A2

Sustainability rating (per m²)

Database ecoinvent

Calculated by HFA

OI3_{Kon}

39.3

dataholz.eu – Catalogue of timber building materials, components and component connections reviewed to consider thermal, acoustic, fire performance requirements and ecological drivers for timber construction released by accredited testing institutes. These datasheets will generally be accepted as proofs of compliance by building authorities.

dataholz.eu

Designation: Last updated: Source: Editor: fdrhbi03b-01 8/2/23 Holzforschung Austria HFA, SP

Details of sustainability rating

Database ecoinvent

Lifecycle	GWP	AP	EP	ODP	POCP	
(Phases)	[kg CO ₂ -e.]	[kg SO ₂ -e.]	[kg PO ₄ -e.]	[kg R11-e.]	[kg Ethen-e.]	
A1 - A3		0.181	0.083	3,08E-6	0.036	
Lifecycle	PERE	PERM	PERT	PENRE	PENRM	PENRT
	[MJ]	[MJ]	[MJ]	[LM]	[M]	[MJ]
(Phases)	[1113]					

dataholz.eu – Catalogue of timber building materials, components and component connections reviewed to consider thermal, acoustic, fire performance requirements and ecological drivers for timber construction released by accredited testing institutes. These datasheets will generally be accepted as proofs of compliance by building authorities.