

Designation: fdrhbi03b-02 Last updated: 8/2/23

Source: Holzforschung Austria

Editor: HFA, SP

Flat roof - fdrhbi03b-02

flat roof, timber frame construction, ventilated, with dry lining, not suspended, other surface

Performance rating


Fire protection

Mass per unit area

 $\begin{array}{c} \textbf{performance} \\ \textbf{maximum span} = 5 \text{ m; maximum load } E_{d,fi} = 3,66 \text{ kN/m}^2 \\ \textbf{Classified by HFA} \\ \\ \textbf{Thermal performance} & \textbf{U} & 0.18 \text{ W/(m}^2 \text{K)} \\ \textbf{Diffusion} & \text{suitable} \\ \\ \textbf{Calculated by HFA} \\ \\ \textbf{Acoustic performance} & \textbf{R}_{\textbf{w}} \textbf{ (C;C}_{\textbf{t'}} \textbf{)} & 48(-2;-6) \text{ dB} \\ \textbf{L}_{\textbf{n,w}} \textbf{ (C_{\textbf{i}})} \\ \textbf{Assessed by TGM} \\ \end{array}$

60

Calculation based on gypsum plaster board type DF



Note: The design of the under-roof construction and of the counterbattens have to be specified according to the roof pitch and the national requirements.

Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

 56.50 kg/m^2

	Thickness	Building material	Thermal performance				Reaction to fire
			λ	μ min – max	ρ	С	EN
Α		Plastic roofing membrane or					E
Α		sheet metal roofing			7800		A1
В	24.0	spruce wood closed cladding without spacing of cladding boards	0.120	50	450	1.600	D
С	80.0	spruce wood counter battens (ventilation)	0.120	50	450	1.600	D
D		sarking membrane sd ≤ 0,3 m			1000		E
Е	15.0	OSB	0.130	200	600	1.700	D
F	240.0	construction timber (80/; e=800)	0.120	50	450	1.600	D
G	240.0	mineral wool [040; ≥16; <1000°C]	0.040	1	16	1.030	A1
Н	15.0	OSB	0.130	200	600	1.700	D
I		vapour barrier sd≥ 11m			1000		
J	24.0	spruce wood cladding with spacing of cladding boards(24/100); a=400	0.120	50	450	1.600	D
K	25.0	gypsum plaster board type DF (2x12,5 mm) or	0.250	10	800	1.050	A2
K	25.0	gypsum fibre board (2x12,5 mm)	0.320	21	1000	1.100	A2

Sustainability rating (per m²)

Database ecoinvent

OI3_{Kon} 40.6

Calculated by HFA



Designation: fdrhbi03b-02 Last updated:

8/2/23 Holzforschung Austria Source:

Editor: HFA, SP

Details of sustainability rating

Database ecoinvent

Lifecycle	GWP	AP	EP	ODP	POCP	
(Phases)	[kg CO ₂ -e.]	[kg SO ₂ -e.]	[kg PO ₄ -e.]	[kg R11-e.]	[kg Ethen-e.]	
A1 - A3		0.187	0.086	3,18E-6	0.037	
Lifecycle	PERE	PERM	PERT	PENRE	PENRM	PENRT
(Phases)	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]
A1 - A3	145.130	755.065	900.194	618.807	30.376	649.183