



Flat roof - fdrhbi05b-01

flat roof, timber frame construction, ventilated, with dry lining, not suspended, other surface

Performance rating

Fire protection performance	REI	60
maximum span = 5 m; maximum load $E_{d,fi} = 3,66 \text{ kN/m}^2$ Classified by HFA		
Thermal performance	U Diffusion	0.18 $\text{W}/(\text{m}^2\text{K})$ suitable
Calculated by HFA		
Acoustic performance	$R_w (C;C_{tr})$ $L_{n,w} (C_i)$	49(-2;-7) dB
Assessed by TGM		
Mass per unit area	m	43.20 kg/m^2
Calculation based on gypsum plaster board type DF		



Note: The design of the under-roof construction and of the counter-battens have to be specified according to the roof pitch and the national requirements.

Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

Thickness	Building material	Thermal performance				Reaction to fire EN
		λ	μ min – max	ρ	c	
A	trapezoidal sheet metal roofing					A1
B	80.0 spruce wood battens (80/50)	0.120	50	450	1.600	D
C	50.0 spruce wood counter battens (ventilation)	0.120	50	450	1.600	D
D	sarking membrane $s_d \leq 0,3\text{m}$			1000		E
E	22.0 softboard [045; 250] - rigid underlay	0.045	5	250	2.100	E
F	220.0 construction timber (80/..; e=800)	0.120	50	450	1.600	D
G	220.0 mineral wool [040; ≥ 16 ; $< 1000^\circ\text{C}$]	0.040	1	16	1.030	A1
I	24.0 spruce wood cladding with spacing of cladding boards(24/100); a=400	0.120	50	450	1.600	D
I	vapour barrier $s_d \geq 2\text{m}$			1000		
J	25.0 gypsum plaster board type DF (2x12,5 mm) or	0.250	10	800	1.050	A2
J	25.0 gypsum fibre board (2x12,5 mm)	0.320	21	1000	1.100	A2

Sustainability rating (per m^2)

Database ecoinvent

O13_{Kon}	73.2
Calculated by HFA	

Details of sustainability rating

Database ecoinvent

Lifecycle (Phases)	GWP [kg CO ₂ -e.]	AP [kg SO ₂ -e.]	EP [kg PO ₄ -e.]	ODP [kg R11-e.]	POCP [kg Ethen-e.]	
A1 - A3		0.287	0.140	4,18E-6	0.049	

Lifecycle (Phases)	PERE [MJ]	PERM [MJ]	PERT [MJ]	PENRE [MJ]	PENRM [MJ]	PENRT [MJ]
A1 - A3	91.384	401.384	492.768	921.416	19.383	940.799