

Designation: fdrhbi05b-01 8/2/23 Last updated:

Holzforschung Austria Source:

Editor: HFA, SP

Flat roof - fdrhbi05b-01

flat roof, timber frame construction, ventilated, with dry lining, not suspended, other surface

Performance rating

Fire protection

performance maximum span = 5 m; maximum load $E_{d,fi}$ = 3,66 kN/m² Classified by HFA Thermal performance U $0.18 \text{ W/(m}^2\text{K)}$ Diffusion suitable Calculated by HFA


60


Acoustic performance R_w (C;C_{tr}) 49(-2;-7) dB $L_{n,w}$ (C_I)

Assessed by TGM

Mass per unit area $43.20~\text{kg/m}^2$

Calculation based on gypsum plaster board type DF





Note: The design of the under-roof construction and of the counterbattens have to be specified according to the roof pitch and the national requirements.

Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

	Thickness	Building material	Thermal performance				Reaction to fire
			λ	μ min – max	ρ	С	EN
Α		trapezoidal sheet metal roofing					A1
В	80.0	spruce wood battens (80/50)	0.120	50	450	1.600	D
С	50.0	spruce wood counter battens (ventilation)	0.120	50	450	1.600	D
D		sarking membrane sd ≤ 0,3 m			1000		E
E	22.0	softboard [045; 250] - rigid underlay	0.045	5	250	2.100	E
F	220.0	construction timber (80/; e=800)	0.120	50	450	1.600	D
G	220.0	mineral wool [040; ≥16; <1000°C]	0.040	1	16	1.030	A1
I	24.0	spruce wood cladding with spacing of cladding boards(24/100); a=400	0.120	50	450	1.600	D
I		vapour barrier sd≥ 2m			1000		
	25.0	gypsum plaster board type DF (2x12,5 mm) or	0.250	10	800	1.050	A2
J	25.0	gypsum fibre board (2x12,5 mm)	0.320	21	1000	1.100	A2

Sustainability rating (per m²)

Database ecoinvent OI3_{Kon} 73.2 Calculated by HFA



Designation: fdrhbi05b-01 Last updated:

8/2/23 Holzforschung Austria Source:

Editor: HFA, SP

Details of sustainability rating

Database ecoinvent

Lifecycle	GWP	AP	EP	ODP	POCP	
(Phases)	[kg CO ₂ -e.]	[kg SO ₂ -e.]	[kg PO ₄ -e.]	[kg R11-e.]	[kg Ethen-e.]	
A1 - A3		0.287	0.140	4,18E-6	0.049	
Lifecycle	PERE	PERM	PERT	PENRE	PENRM	PENRT
(Phases)	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]
A1 - A3	91.384	401.384	492.768	921.416	19.383	940.799