

Designation: fdrhbi06a-01 Last updated: 8/2/23

Source: Holzforschung Austria

Editor: HFA, SP

Flat roof - fdrhbi06a-01

flat roof, timber frame construction, ventilated, with dry lining, not suspended, other surface

Performance rating


Fire protection REI 30 performance


maximum span = 5 m; maximum load E_{d,fi} = 2,62 kN/m²

Classified by HFA

Thermal performance	U Diffusion	0.21 W/(m ² K) suitable
Calculated by HFA		
Acoustic performance	R _w (C;C _{tr}) L _{n,w} (C _I)	45(-3;-7) dB
Assessed by TGM		
Mass per unit area	m	45.90 kg/m ²

Calculation based on gypsum plaster board type DF





Note: The design of the under-roof construction and of the counterbattens have to be specified according to the roof pitch and the national requirements. K=without insulation

Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

	Thickness	Building material	Thermal per	formance			Reaction to fire
			λ	μ min – max	ρ	С	EN
Α		sheet metal roofing or			7800		A1
Α		Plastic roofing membrane					E
В	24.0	spruce wood closed cladding without spacing of cladding boards	0.120	50	450	1.600	D
С	80.0	spruce wood counter battens (ventilation)	0.120	50	450	1.600	D
D		sarking membrane sd ≤ 0,3m			1000		E
E	15.0	OSB	0.130	200	600	1.700	D
F	200.0	construction timber (80/; e=800)	0.120	50	450	1.600	D
G	200.0	mineral wool [040; ≥16; <1000 °C]	0.040	1	16	1.030	A1
Н		vapour barrier sd≥ 8m			1000		
I	15.0	OSB	0.130	200	600	1.700	D
J	50.0	spruce wood cross battens (50/80;a=400)	0.120	50	450	1.600	D
K		without insulation					
L	12.5	gypsum plaster board type DF or	0.250	10	800	1.050	A2
L	12.5	gypsum fibre board	0.320	21	1000	1.100	A2

Sustainability rating (per m²)

Database ecoinvent
Ol3_{Kon} 35.8

Calculated by HFA



Designation: fdrhbi06a-01 Last updated:

8/2/23 Holzforschung Austria Source:

HFA, SP Editor:

Details of sustainability rating

Database ecoinvent

Lifecycle	GWP	AP	EP	ODP	POCP	
(Phases)	[kg CO ₂ -e.]	[kg SO ₂ -e.]	[kg PO ₄ -e.]	[kg R11-e.]	[kg Ethen-e.]	
A1 - A3		0.172	0.079	2,74E-6	0.035	
		ı	I	1 .	ı	T.
Lifecycle	PERE	PERM	PERT	PENRE	PENRM	PENRT
Lifecycle (Phases)	PERE [MJ]	PERM [MJ]	PERT [MJ]	PENRE	PENRM [MJ]	PENRT [MJ]