

Designation: fdrhbi06a-07 Last updated: 8/2/23

Source: Holzforschung Austria

Editor: HFA, SP

Flat roof - fdrhbi06a-07

flat roof, timber frame construction, ventilated, with dry lining, not suspended, other surface

Performance rating

Fire protection


 $\begin{array}{c} \textbf{performance} \\ \textbf{maximum span} = 5 \text{ m; maximum load } E_{d,fi} = 2,62 \text{ kN/m}^2 \\ \textbf{Classified by HFA} \\ \hline \\ \textbf{Thermal performance} & \textbf{U} & 0.20 \text{ W/(m}^2\text{K)} \\ \textbf{Diffusion} & \text{suitable} \\ \hline \\ \textbf{Acoustic performance} & \textbf{R}_{\textbf{w}} \textbf{(C;C}_{\textbf{tr}} \textbf{)} & 46(-3;-7) \text{ dB} \\ \end{array}$


30

Assessed by TGM

 $L_{n,w}$ (C_I)

Calculation based on gypsum plaster board type DF





Note: The design of the under-roof construction and of the counterbattens have to be specified according to the roof pitch and the national requirements.

Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

	Thickness	Building material	Thermal per	formance			Reaction to fire
			λ	μ min – max	ρ	С	EN
Α		sheet metal roofing or			7800		A1
Α		Plastic roofing membrane					E
В	24.0	spruce wood closed cladding without spacing of cladding boards	0.120	50	450	1.600	D
С	80.0	spruce wood counter battens (ventilation)	0.120	50	450	1.600	D
D		sarking membrane sd ≤ 0,3 m			1000		Е
Е	15.0	OSB	0.130	200	600	1.700	D
F	200.0	construction timber (80/; e=800)	0.120	50	450	1.600	D
G	200.0	sheep wool [0,041; R=26]	0.041	1	30	1.720	E
Н		vapour barrier sd≥ 8m			1000		
I	15.0	OSB	0.130	200	600	1.700	D
J	50.0	spruce wood cross battens (50/80;a=400)	0.120	50	450	1.600	D
K	50.0	sheep wool [0,041; R=26]	0.041	1	30	1.720	E
L	12.5	gypsum plaster board type DF or	0.250	10	800	1.050	A2
L	12.5	gypsum fibre board	0.320	21	1000	1.100	A2

Sustainability rating (per m²)

Database ecoinvent

Ol3_{Kon} 31.2

Calculated by HFA



Designation: fdrhbi06a-07 Last updated:

8/2/23 Holzforschung Austria Source:

HFA, SP Editor:

Details of sustainability rating

Database ecoinvent

Lifecycle	GWP	AP	EP	ODP	POCP	
(Phases)	[kg CO ₂ -e.]	[kg SO ₂ -e.]	[kg PO ₄ -e.]	[kg R11-e.]	[kg Ethen-e.]	
A1 - A3		0.148	0.067	2,76E-6	0.034	
Lifecycle	PERE	PERM	PERT	PENRE	PENRM	PENRT
(Phases)	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]
A1 - A3	138.843	890.116	1028.959	529.793	32.546	562.339