

Designation: fdrhbi06b-01 Last updated: 8/2/23

Source: Holzforschung Austria

Editor: HFA, SP

Flat roof - fdrhbi06b-01

flat roof, timber frame construction, ventilated, with dry lining, not suspended, other surface

Performance rating

Fire protection

 $\begin{array}{c} \textbf{performance} \\ \textbf{maximum span} = 5 \text{ m; maximum load } E_{d,fi} = 3,66 \text{ kN/m}^2 \\ \textbf{Classified by HFA} \\ \hline \textbf{Thermal performance} \qquad \textbf{U} \\ \textbf{Diffusion} \qquad \textbf{Suitable} \\ \textbf{Calculated by HFA} \\ \end{array}$

60

46(-3;-7) dB

REI

 $L_{n,w}$ (C_{l})


Acoustic performance


Assessed by TGM

Mass per unit area m 55.80 kg/m²

 R_w (C;C_{tr})

Calculation based on gypsum plaster board type DF





Note: The design of the under-roof construction and of the counterbattens have to be specified according to the roof pitch and the national requirements. K=without insulation

Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

T	hickness	Building material	Thermal performance				Reaction to fire
			λ	μ min – max	ρ	С	EN
4		Plastic roofing membrane or					E
4		sheet metal roofing			7800		A1
В	24.0	spruce wood closed cladding without spacing of cladding boards	0.120	50	450	1.600	D
С	80.0	spruce wood counter battens (ventilation)	0.120	50	450	1.600	D
D		sarking membrane sd ≤ 0,3 m			1000		E
E	15.0	OSB	0.130	200	600	1.700	D
F	200.0	construction timber (80/; e=800)	0.120	50	450	1.600	D
G	200.0	mineral wool [040; ≥16; <1000°C]	0.040	1	16	1.030	A1
Н		vapour barrier sd≥ 8m			1000		
	15.0	OSB	0.130	200	600	1.700	D
J	50.0	spruce wood cross battens (50/80;a=400)	0.120	50	450	1.600	D
K		without insulation					
L	25.0	gypsum plaster board type DF (2x12,5 mm) or	0.250	10	800	1.050	A2
	25.0	gypsum fibre board (2x12,5 mm)	0.320	21	1000	1.100	A2

Sustainability rating (per m²)

Database ecoinvent
OI3_{Kon} 38.1

Calculated by HFA

dataholz.eu – Catalogue of timber building materials, components and component connections reviewed to consider thermal, acoustic, fire performance requirements and ecological drivers for timber construction released by accredited testing institutes.



Designation: fdrhbi06b-01 Last updated:

8/2/23 Holzforschung Austria Source:

HFA, SP Editor:

Details of sustainability rating

Database ecoinvent

Lifecycle	GWP	AP	EP	ODP	POCP	
(Phases)	[kg CO ₂ -e.]	[kg SO ₂ -e.]	[kg PO ₄ -e.]	[kg R11-e.]	[kg Ethen-e.]	
A1 - A3		0.177	0.081	3,01E-6	0.036	
Lifecycle	PERE	PERM	PERT	PENRE	PENRM	PENRT
(Phases)	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]
A1 - A3	143.791	755.065	898.856	590.043	31.226	621.268