

Designation: fdrhbi06b-06 Last updated: 8/2/23

Source: Holzforschung Austria

Editor: HFA, SP

## Flat roof - fdrhbi06b-06

flat roof, timber frame construction, ventilated, with dry lining, not suspended, other surface

## Performance rating


Fire protection

 $\begin{array}{c} \textbf{performance} \\ \textbf{maximum span} = 5 \text{ m; maximum load } E_{d,fi} = 3,66 \text{ kN/m}^2 \\ \textbf{Classified by HFA} \\ \hline \\ \textbf{Thermal performance} & \textbf{U} & 0.18 \text{ W/(m}^2\text{K)} \\ \textbf{Diffusion} & \text{suitable} \\ \hline \\ \textbf{Calculated by HFA} \\ \hline \\ \textbf{Acoustic performance} & \textbf{R}_{\textbf{w}} \textbf{ (C;C}_{tr} \textbf{)} & 47(-2;-6) \text{ dB} \\ \textbf{L}_{\textbf{n,w}} \textbf{ (C_l)} \\ \hline \end{array}$ 

60

Assessed by TGM

Calculation based on gypsum plaster board type DF



Note: The design of the under-roof construction and of the counterbattens have to be specified according to the roof pitch and the national requirements.

### Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

	Thickness	Building material	Thermal performance				Reaction to fire	
			λ	μ min – max	ρ	С	EN	
Α		Plastic roofing membrane or					E	
Α		sheet metal roofing			7800		A1	
В	24.0	spruce wood closed cladding without spacing of cladding boards	0.120	50	450	1.600	D	
С	80.0	spruce wood counter battens (ventilation)	0.120	50	450	1.600	D	
D		sarking membrane sd ≤ 0,3 m			1000		Е	
Е	15.0	OSB	0.130	200	600	1.700	D	
F	200.0	construction timber (80/; e=800)	0.120	50	450	1.600	D	
G	200.0	cellulose fibre [040; E]	0.040	1 - 2	55	2.000	E	
Н		vapour barrier sd≥ 8m			1000			
I	15.0	OSB	0.130	200	600	1.700	D	
J	50.0	spruce wood cross battens (50/80;a=400)	0.120	50	450	1.600	D	
K	50.0	cellulose fibre [040; E]	0.040	1 - 2	55	2.000	E	
L	25.0	gypsum plaster board type DF (2x12,5 mm) or	0.250	10	800	1.050	A2	
L	25.0	gypsum fibre board (2x12,5 mm)	0.320	21	1000	1.100	A2	

### Sustainability rating (per m<sup>2</sup>)

# Database ecoinvent Ol3<sub>Kon</sub> 32.5 Calculated by HFA

dataholz.eu – Catalogue of timber building materials, components and component connections reviewed to consider thermal, acoustic, fire performance requirements and ecological drivers for timber construction released by accredited testing institutes.



Designation: fdrhbi06b-06 Last updated:

8/2/23 Holzforschung Austria Source:

Editor: HFA, SP

### Details of sustainability rating

#### Database ecoinvent

Lifecycle	GWP	AP	EP	ODP	POCP	
(Phases)	[kg CO <sub>2</sub> -e.]	[kg SO <sub>2</sub> -e.]	[kg PO <sub>4</sub> -e.]	[kg R11-e.]	[kg Ethen-e.]	
A1 - A3		0.168	0.075	2,68E-6	0.033	
Lifecycle	PERE	PERM	PERT	PENRE	PENRM	PENRT
	FA 4 13	FNAID	[MJ]	[MJ]	[MJ]	[MJ]
(Phases)	[MJ]	[MJ]	[INI]	[LIAI2]	[IAD]	[INI]