dataholz.eu


fdrhbi08a-03 8/2/23 Holzforschung Austria HFA, SP

Flat roof - fdrhbi08a-03

flat roof, timber frame construction, ventilated, with dry lining, not suspended, other surface

Performance rating

Fire protection performance	REI	30
maximum span = 5 m; ma Classified by HFA	aximum load E _{d,fi} = 3,66 kN	l∕m²
Thermal performance	U Diffusion	0.16 W∕(m ² K) suitable
Calculated by HFA		
Acoustic performance	R _w (C;C _{tr}) L _{n,w} (C _l)	50(-2;-7) dB
Assessed by TGM		
Mass per unit area	m	40.20 kg∕m ²
Calculation based on GF		



Note: The design of the under-roof construction and of the counterbattens have to be specified according to the roof pitch and the national requirements.

Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

	Thickness	Building material	Thermal per	formance			Reaction to fire
			λ	µ min – max	ρ	c	EN
		Plastic roofing membrane or					E
		sheet metal roofing			7800		A1
	24.0	spruce wood closed cladding without spacing of cladding boards	0.120	50	450	1.600	D
	80.0	spruce wood counter battens (ventilation)	0.120	50	450	1.600	D
)		sarking membrane sd \leq 0,3m			1000		E
)	15.0	fibreboard (MDF)	0.140	11	600	1.700	D
	240.0	construction timber (80/*; e=800)	0.120	50	450	1.600	D
	240.0	mineral wool [040; ≥16; <1000 °C]	0.040	1	16	1.030	A1
;		vapour barrier sd≥ 1 m			1000		
1	50.0	spruce wood cross battens (50/80;a=400)	0.120	50	450	1.600	D
	50.0	mineral wool [040; \geq 16; <1000 °C] or without insulation in type 01	0.040	1	16	1.030	A1
	12.5	gypsum fibre board or	0.320	21	1000	1.100	A2
	12.5	gypsum plaster board type DF	0.250	10	800	1.050	A2

Sustainability rating (per m²)

Database ecoinvent

OI3_{Kon}

Calculated by HFA

38.9

dataholz.eu – Catalogue of timber building materials, components and component connections reviewed to consider thermal, acoustic, fire performance requirements and ecological drivers for timber construction released by accredited testing institutes. These datasheets will generally be accepted as proofs of compliance by building authorities.

dataholz.eu

Designation: Last updated: Source: Editor: fdrhbi08a-03 8/2/23 Holzforschung Austria HFA, SP

Details of sustainability rating

Database ecoinvent

Lifecycle	GWP	AP	EP	ODP	POCP	
(Phases)	[kg CO ₂ -e.]	[kg SO ₂ -e.]	[kg PO ₄ -e.]	[kg R11-e.]	[kg Ethen-e.]	
A1 - A3		0.180	0.084	2,73E-6	0.033	
Lifecycle	PERE	PERM	PERT	PENRE	PENRM	PENRT
(Phases)	[LM]	[LM]	[MJ]	[LM]	[LM]	[M]
(,				567.451	29.762	597.213

dataholz.eu – Catalogue of timber building materials, components and component connections reviewed to consider thermal, acoustic, fire performance requirements and ecological drivers for timber construction released by accredited testing institutes. These datasheets will generally be accepted as proofs of compliance by building authorities.