

Designation: fdrhbi08a-05 Last updated: 8/2/23

Source: Holzforschung Austria

Editor: HFA, SP

Flat roof - fdrhbi08a-05

flat roof, timber frame construction, ventilated, with dry lining, not suspended, other surface

Performance rating


Fire protection

30

Assessed by TGM

 $\label{eq:mass_per_unit_area} \mbox{Mass per unit area} \qquad \mbox{m} \qquad \qquad 41.40 \mbox{ kg/m}^2$

Calculation based on GF



Note: The design of the under-roof construction and of the counterbattens have to be specified according to the roof pitch and the national requirements.

Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

Thi	Thickness	Building material	Thermal performance				Reaction to fire	
			λ	μ min – max	ρ	С	EN	
4		Plastic roofing membrane or					E	
4		sheet metal roofing			7800		A1	
3	24.0	spruce wood closed cladding without spacing of cladding boards	0.120	50	450	1.600	D	
	80.0	spruce wood counter battens (ventilation)	0.120	50	450	1.600	D	
)		sarking membrane $sd \le 0,3m$			1000		Е	
)	15.0	fibreboard (MDF)	0.140	11	600	1.700	D	
	200.0	construction timber (80/*; e=800)	0.120	50	450	1.600	D	
=	200.0	mineral wool [038; ≥33; ≥1000°C]	0.038	1	33	1.030	A1	
5		vapour barrier sd≥ 1 m			1000			
1	50.0	spruce wood cross battens (50/80;a=400)	0.120	50	450	1.600	D	
	50.0	mineral wool [038; ≥33; ≥1000°C] or without insulation in type 01	0.038	1	33	1.030	A1	
	12.5	gypsum fibre board or	0.320	21	1000	1.100	A2	
	12.5	gypsum plaster board type DF	0.250	10	800	1.050	A2	

Sustainability rating (per m²)

Database ecoinvent
Ol3_{Kon} 43.6

Calculated by HFA



Designation: fdrhbi08a-05 Last updated:

8/2/23 Holzforschung Austria Source:

HFA, SP Editor:

Details of sustainability rating

Database ecoinvent

Lifecycle	GWP	AP	EP	ODP	POCP	
(Phases)	[kg CO ₂ -e.]	[kg SO ₂ -e.]	[kg PO ₄ -e.]	[kg R11-e.]	[kg Ethen-e.]	
A1 - A3		0.213	0.079	2,12E-6	0.069	
Lifecycle	PERE	PERM	PERT	PENRE	PENRM	PENRT
(Phases)	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]
A1 - A3	103.710	638.476	742.187	539.757	29.762	569.519