

Designation: fdrhbi08b-00 Last updated: 8/2/23

Source: Holzforschung Austria

Editor: HFA, SP

Flat roof - fdrhbi08b-00


flat roof, timber frame construction, ventilated, with dry lining, not suspended, other surface


Performance rating

Calculation based on GF

Fire protection

60





Note: The design of the under-roof construction and of the counterbattens have to be specified according to the roof pitch and the national requirements.

Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

	Thickness	Building material	Thermal performance				Reaction to fire	
			λ μ min – max ρ		ρ	С	EN	
Α		Plastic roofing membrane or					E	
Α		sheet metal roofing			7800		A1	
В	24.0	spruce wood closed cladding without spacing of cladding boards	0.120	50	450	1.600	D	
С	80.0	spruce wood counter battens (ventilation)	0.120	50	450	1.600	D	
D		sarking membrane sd ≤ 0,3m			1000		Е	
D	15.0	fibreboard (MDF)	0.140	11	600	1.700	D	
E	200.0	construction timber (80/*; e=800)	0.120	50	450	1.600	D	
F	200.0	mineral wool [040; ≥16; <1000°C]	0.040	1	16	1.030	A1	
G		vapour barrier sd≥ 1 m			1000			
Н	50.0	spruce wood cross battens (50/80;a=400)	0.120	50	450	1.600	D	
I	50.0	mineral wool [040; \geq 16; <1000 °C] or without insulation in type 01	0.040	1	16	1.030	A1	
J	25.0	gypsum fibre board (2x12,5 mm) or	0.320	21	1000	1.100	A2	
J	25.0	gypsum plaster board type DF (2x12,5 mm)	0.250	10	800	1.050	A2	

Sustainability rating (per m²)

Database ecoinvent

OI3_{Kon} 38.8

Calculated by HFA



Designation: fdrhbi08b-00 8/2/23 Holzforschung Austria Last updated:

Source:

Editor: HFA, SP

Details of sustainability rating

Database ecoinvent

Lifecycle	GWP	AP	EP	ODP	POCP	
(Phases)	[kg CO ₂ -e.]	[kg SO ₂ -e.]	[kg PO ₄ -e.]	[kg R11-e.]	[kg Ethen-e.]	
A1 - A3		0.174	0.082	2,80E-6	0.031	
Lifecycle	PERE	PERM	PERT	PENRE	PENRM	PENRT
(Phases)	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]