

Designation: fdrhbi10b-03 Last updated: 8/2/23

Source: Holzforschung Austria

Editor: HFA, SP

Flat roof - fdrhbi10b-03

flat roof, timber frame construction, ventilated, with dry lining, not suspended, other surface

Performance rating

Fire protection

Mass per unit area

Calculation based on GF

60

B C D

Note: The design of the under-roof construction and of the counterbattens have to be specified according to the roof pitch and the national requirements.

H/I

Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

 59.80 kg/m^2

	Thickness	Building material	Thermal performance				Reaction to fire	
			λ	μ min – max	ρ	С	EN	
4		Plastic roofing membrane or					E	
A		sheet metal roofing			7800		A1	
В	24.0	spruce wood closed cladding without spacing of cladding boards	0.120	50	450	1.600	D	
С	80.0	spruce wood counter battens (ventilation)	0.120	50	450	1.600	D	
D		sarking membrane sd ≤ 0,3m			1000		E	
D	15.0	fibreboard (MDF)	0.140	11	600	1.700	D	
Е	240.0	construction timber (80/; e=800)	0.120	50	450	1.600	D	
F	240.0	mineral wool [040; ≥16; <1000°C]	0.040	1	16	1.030	A1	
G	15.0	OSB (sealed with airtight tape)	0.130	200	600	1.700	D	
+	50.0	spruce wood cross battens (50/80;a=400)	0.120	50	450	1.600	D	
	50.0	mineral wool [040; ≥16; <1000°C]	0.040	1	16	1.030	A1	
	25.0	gypsum plaster board type DF (2x12,5 mm) or	0.250	10	800	1.050	A2	
J	25.0	gypsum fibre board (2x12,5 mm)	0.320	21	1000	1.100	A2	

Sustainability rating (per m²)

Database ecoinvent

OI3_{Kon} 44.1

Calculated by HFA



Designation: fdrhbi10b-03 Last updated:

8/2/23 Holzforschung Austria Source:

Editor: HFA, SP

Details of sustainability rating

Database ecoinvent

Lifecycle	GWP	AP	EP	ODP	POCP	
(Phases)	[kg CO ₂ -e.]	[kg SO ₂ -e.]	[kg PO ₄ -e.]	[kg R11-e.]	[kg Ethen-e.]	
A1 - A3		0.203	0.094	3,31E-6	0.037	
Lifecycle	PERE	PERM	PERT	PENRE	PENRM	PENRT
(Phases)	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]
, , , , ,						