

## Intermediate floor - gdmnxa03a-04

intermediate floor, solid wood construction, suspended, wet, with filling, other surface

### Performance rating

**Fire protection performance** REI 90  
 maximum span = 5 m; maximum load  $E_{d,fi} = 6,5 \text{ kN/m}^2$  (without floor construction)  
 Classified by HFA

**Thermal performance** U Diffusion 0.34 W/(m<sup>2</sup>K)  
 suitable


Calculated by HFA

**Acoustic performance**  $R_w$  (C;C<sub>tr</sub>) 77(-5;12) dB  
 $L_{n,w}$  (C<sub>i</sub>) 43(2)

[C<sub>150-2500</sub>] = [9] dB  
 Assessed by HFA

**Mass per unit area** m 336.70 kg/m<sup>2</sup>

Calculation based on gypsum plaster board type DF



Note: D: fill m' approx. 93 kg/m<sup>2</sup>

### Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

	Thickness	Building material	Thermal performance				Reaction to fire EN
			$\lambda$	$\mu$ min – max	$\rho$	c	
A	60.0	cement screed m' ca. 150 kg/m <sup>2</sup>	1.330	50 - 100	2500	1.080	
B		plastic separation layer	0.200	100000	1400	1.400	E
C	30.0	impact sound absorbing subflooring MW-T [s' = 10 MN/m <sup>3</sup> ]	0.033	1	70	1.030	A1
D	60.0	non-bonded chippings	0.700	1	1550	1.000	A1
E		trickling protection					E
F	160.0	cross laminated timber 5-ply (first layer minimum 40 mm)	0.130	50	500	1.600	D
G	27.0	resilient channel (a=400)					
H	25.0	mineral wool [040; ≥16; <1000°C]	0.040	1	16	1.030	A1
I	12.5	gypsum plaster board type DF or	0.250	10	800	1.050	A2
I	12.5	gypsum fibre board	0.320	21	1000	1.100	A2

### Sustainability rating (per m<sup>2</sup>)

#### Database ecoinvent

013<sub>kon</sub> 61.2

Calculated by HFA

## Details of sustainability rating

### Database ecoinvent

Lifecycle (Phases)	GWP [kg CO <sub>2</sub> -e.]	AP [kg SO <sub>2</sub> -e.]	EP [kg PO <sub>4</sub> -e.]	ODP [kg R11-e.]	POCP [kg Ethen-e.]	
A1 - A3		0.275	0.124	4,65E-6	0.073	

Lifecycle (Phases)	PERE [MJ]	PERM [MJ]	PERT [MJ]	PENRE [MJ]	PENRM [MJ]	PENRT [MJ]
A1 - A3	66.255	1094.400	1160.655	943.378	52.971	996.348