dataholz.eu

gdrnxa07a-13 8/2/23 Holzforschung Austria HFA, SP

Intermediate floor - gdrnxa07a-13

intermediate floor, timber frame construction, suspended, wet, with filling, other surface

Performance rating

Fire protection performance	REI	30
maximum span = 5 m construction; with ceil Classified by HFA Classified by HFA	; maximum load E _{d,fi} ing beam 80/200)	= 3,66 kN/m² (without floor
Germany		
F30		
Load E _{d,fi} according to	the German certifica	ation document

Corresponding proof: DIN 4102-4:2016-05, Tabelle 10.12, Zeile 1

Thermal performance	U Diffusion	suitable			
Calculated by HFA					
Acoustic performance	R _w (C;C _{tr}) L _{n,w} (C _l)	69(-1;-6) dB 42(2)			
Assessed by Müller-BBM					
Mass per unit area	m	197.60 kg/m ²			





Calculation based on gypsum plaster board type DF

Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

	Thickness	Building material	Thermal per	Reaction to fire			
			λ	µ min – max	ρ	с	EN
А	50.0	cement screed or anhydrite screed	1.330	50 - 100	2000	1.080	A1
В		plastic separation layer	0.200	100000	1400	1.400	E
С	40.0	impact sound absorbing subflooring MW-T [s' = 10 MN/m ³]	0.035	1	68	1.030	A1
D	30.0	fill loose	0.700	1	1800	1.000	A1
Е		trickling protection					E
F	18.0	OSB	0.130	200	600	1.700	D
G	240.0	construction timber (80/; e=625)	0.120	50	450	1.600	D
Н	100.0	mineral wool [040; 30; ≥1000°C]	0.040	1	30	1.030	A1
Ι	24.0	0 spruce wood cladding with spacing of cladding boards(24/100); a=400		50	450	1.600	D
J	27.0	resilient channel placed between cladding with spacing	0.156				
К	12.5	gypsum plaster board type DF or	0.250	10	800	1.050	A2
Κ	12.5	gypsum fibre board	0.320	21	1000	1.100	A2

Sustainability rating (per m²)

Database GaBi (ÖKOBAUDAT) Database ecoinvent OI3_{Kon} 42.7 **Built-in renewable materials** 28.850 kg kg CO₂ 43.060 Biogenic carbon in kg CO₂-e. Calculated by HFA 687.480 Energy use of Primary Energy MJ Share of renewable PE % 21.71

dataholz.eu – Catalogue of timber building materials, components and component connections reviewed to consider thermal, acoustic, fire performance requirements and ecological drivers for timber construction released by accredited testing institutes.

These datasheets will generally be accepted as proofs of compliance by building authorities.

dataholz.eu

Designation: Last updated: Source: Editor: gdrnxa07a-13 8/2/23 Holzforschung Austria HFA, SP

Details of sustainability rating

Database ecoinvent

Lifecycle	GWP	AP	EP	ODP	POCP	
(Phases)	[kg CO ₂ -e.]	[kg SO ₂ -e.]	[kg PO ₄ -e.]	[kg R11-e.]	[kg Ethen-e.]	
A1 - A3		0.178	0.079	2,67E-6	0.041	
Lifecycle	PERE	PERM	PERT	PENRE	PENRM	PENRT
(Phases)	[MJ]	[MJ]	[M]	[LM]	[MJ]	[M]
A1 - A3	112.159	476.516	588.676	571.067	20.654	591.721

Database GaBi (ÖKOBAUDAT)

Lifecycle	GWP	AP	EP	ODP	POCP	
(Phases)	[kg CO ₂ -e.]	[kg SO ₂ -e.]	[kg PO ₄ -e.]	[kg R11-e.]	[kg Ethen-e.]	
A1 - A3		0.147	0.021	9,23E-7	0.023	
C1 - C4		0.015	0.005	6,77E-8	0.002	
A1 - C4		0.167	0.027	9,99E-7	0.024	
Lifecycle	PERE	PERM	PERT	PENRE	PENRM	PENRT
(Phases)	[M]	[LM]	[M]	[M]	[MJ]	[MJ]
A1 - A3	146.672	505.236	653.438	509.559	54.744	564.451
C1 - C4	2.217	-498.594	-495.237	22.682	-7.744	30.538
A1 - C4	149.274	6.902	159.328	538.204	47.052	609.144