

Intermediate floor - gdrnxa07a-14

intermediate floor, timber frame construction, suspended, wet, with filling, other surface

Performance rating

Fire protection performance REI 30

maximum span = 5 m; maximum load $E_{d,fi}$ = 3,66 kN/m² (without floor construction; with ceiling beam 80/200)

Classified by HFA

Classified by HFA

Germany

F30

Load $E_{d,fi}$ according to the German certification document

Corresponding proof: DIN 4102-4:2016-05, Tabelle 10.12, Zeile 1

Thermal performance U Diffusion suitable



Calculated by HFA

Acoustic performance R_w (C;C_{tr}) 69(-1;-6) dB
 $L_{n,w}$ (C_i) 42(2)

Assessed by Müller-BBM

Mass per unit area m 199.30 kg/m²

Calculation based on gypsum plaster board type DF



Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

	Thickness	Building material	Thermal performance				Reaction to fire EN
			λ	μ min – max	ρ	c	
A	50.0	cement screed or anhydrite screed	1.330	50 - 100	2000	1.080	A1
B		plastic separation layer	0.200	100000	1400	1.400	E
C	40.0	impact sound absorbing subflooring MW-T (s' = 10 MN/m ³)	0.035	1	68	1.030	A1
D	30.0	fill loose	0.700	1	1800	1.000	A1
E		trickling protection					E
F	18.0	OSB	0.130	200	600	1.700	D
G	240.0	construction timber (80/...; e=625)	0.120	50	450	1.600	D
H	100.0	Cellulose fibre [040; 50]	0.040	1	50	2.000	E
I	24.0	spruce wood cladding with spacing of cladding boards(24/100); a=400	0.120	50	450	1.600	D
J	27.0	resilient channel placed between cladding with spacing	0.156				
K	12.5	gypsum plaster board type DF or	0.250	10	800	1.050	A2
K	12.5	gypsum fibre board	0.320	21	1000	1.100	A2

Sustainability rating (per m²)

Database ecoinvent

Ol3_{Kon} 38.5

Calculated by HFA

Database GaBi (ÖKOBAUDAT)

Built-in renewable materials	kg	34.520
Biogenic carbon in kg CO ₂ -e.	kg CO ₂	50.160
Energy use of Primary Energy	MJ	655.310
Share of renewable PE	%	22.88

Details of sustainability rating

Database ecoinvent

Lifecycle (Phases)	GWP [kg CO ₂ -e.]	AP [kg SO ₂ -e.]	EP [kg PO ₄ -e.]	ODP [kg R11-e.]	POCP [kg Ethen-e.]	
A1 - A3		0.161	0.077	2,67E-6	0.029	
Lifecycle (Phases)	PERE [MJ]	PERM [MJ]	PERT [MJ]	PENRE [MJ]	PENRM [MJ]	PENRT [MJ]
A1 - A3	114.580	519.976	634.556	544.007	20.654	564.661

Database GaBi (ÖKOBAUDAT)

Lifecycle (Phases)	GWP [kg CO ₂ -e.]	AP [kg SO ₂ -e.]	EP [kg PO ₄ -e.]	ODP [kg R11-e.]	POCP [kg Ethen-e.]	
A1 - A3		0.129	0.019	8,16E-7	0.022	
C1 - C4		0.016	0.007	7,73E-8	0.002	
A1 - C4		0.150	0.027	9,01E-7	0.023	
Lifecycle (Phases)	PERE [MJ]	PERM [MJ]	PERT [MJ]	PENRE [MJ]	PENRM [MJ]	PENRT [MJ]
A1 - A3	147.317	576.747	725.612	475.955	50.466	526.570
C1 - C4	2.215	-498.594	-495.240	23.981	-7.744	31.837
A1 - C4	149.913	78.412	231.496	505.396	42.774	572.058