

Designation: gdrnxa07a-06 Last updated: 8/2/23

Holzforschung Austria Source:

Editor: HFA, SP

# Intermediate floor - gdrnxa07a-06

intermediate floor, timber frame construction, suspended, wet, with filling, other surface


### Performance rating


Fire protection REI 30 performance

maximum span = 5 m; maximum load  $E_{d,fi}$  = 3,66 kN/m² (without floor construction; with ceiling beam 80/200)br> Classified by IBS Classified by HFA

Thermal performance	U Diffusion	0.28 W/(m <sup>2</sup> K) suitable
Calculated by HFA		
Acoustic performance	R <sub>w</sub> (C;C <sub>tr</sub> ) L <sub>n,w</sub> (C <sub>I</sub> )	70(-2;-7) dB 41(1)
Assessed by TGM		
Mass per unit area	m	214.40 kg/m <sup>2</sup>

Calculation based on gypsum plaster board type DF





# Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

	Thickness	Building material	Thermal per	rformance			Reaction to fire
			λ	μ min – max	ρ	С	EN
Α	50.0	cement screed or anhydrite screed	1.330	50 - 100	2000	1.080	A1
В		plastic separation layer	0.200	100000	1400	1.400	E
С	30.0	impact sound absorbing subflooring MW-T [s'=10 MN/m³]	0.035	1	68	1.030	A1
D	40.0	fill loose	0.700	1	1800	1.000	A1
Е		trickling protection					E
F	18.0	OSB	0.130	200	600	1.700	D
G	220.0	construction timber (80/; e=625)	0.120	50	450	1.600	D
Н	100.0	sheep wool [0,041; R=26]	0.041	1	30	1.720	E
I	24.0	spruce wood cladding with spacing of cladding boards(24/100); a=400	0.120	50	450	1.600	D
J	27.0	resilient channel placed between cladding with spacing	0.156				
K	12.5	gypsum plaster board type DF or	0.250	10	800	1.050	A2
K	12.5	gypsum fibre board	0.320	21	1000	1.100	A2

## Sustainability rating (per m²)

Database ecoinvent

Calculated by HFA

OI3<sub>Kon</sub>

34.9



Designation: gdrnxa07a-06 Last updated:

8/2/23 Holzforschung Austria Source:

HFA, SP Editor:

### Details of sustainability rating

#### Database ecoinvent

Lifecycle	GWP	AP	EP	ODP	POCP	
(Phases)	[kg CO <sub>2</sub> -e.]	[kg SO <sub>2</sub> -e.]	[kg PO <sub>4</sub> -e.]	[kg R11-e.]	[kg Ethen-e.]	
A1 - A3		0.140	0.068	2,48E-6	0.027	
Lifecycle	PERE	PERM	PERT	PENRE	PENRM	PENRT
(Phases)	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]
A1 - A3	105.648	487.670	593.318	506.174	20.968	527.142