

## Intermediate floor - gdrtn03b-03

intermediate floor, timber frame construction, not suspended, dry, without filling, other surface

### Performance rating

**Fire protection performance** REI 60

maximum span = 5 m; maximum load  $E_{d,fi} = 3,66 \text{ kN/m}^2$   
Classified by HFA

**Thermal performance** U 0.25 W/(m<sup>2</sup>K)  
Diffusion suitable



Calculated by HFA

**Acoustic performance**  $R_w (C; C_{tr})$  50(-2;-9) dB  
 $L_{n,w} (C_i)$  66(0)

Assessed by TGM

**Mass per unit area** m 76.90 kg/m<sup>2</sup>

Calculation based on GF



Note: e=625;

### Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

|   | Thickness | Building material  | Thermal performance |                 |        |       | Reaction to fire<br>EN |
|---|-----------|--|---------------------|-----------------|--------|-------|------------------------|
|   |           |  | $\lambda$           | $\mu$ min – max | $\rho$ | c     |                        |
| A | 25.0      | dry screed   | 0.210               | 8               | 900    | 1.050 | A1                     |
| B | 30.0      | impact sound absorbing subflooring MW-T                                | 0.035               | 1               | 68     | 1.030 | A1                     |
| C | 19.0      | particleboard  | 0.130               | 50 - 100        | 700    | 1.700 | D                      |
| D | 220.0     | construction timber (80/...; e=*)                                      | 0.120               | 50              | 450    | 1.600 | D                      |
| E | 100.0     | mineral wool [035; 50; <1000°C]  | 0.035               | 1               | 50     | 1.030 | A1                     |
| F | 24.0      | spruce wood cladding with spacing of cladding boards(24/100);<br>a=400 | 0.120               | 50              | 450    | 1.600 | D                      |
| G | 25.0      | gypsum plaster board type DF (2x12,5 mm) or                            | 0.250               | 10              | 800    | 1.050 | A2                     |
| G | 25.0      | gypsum fibre board (2x12,5 mm)   | 0.320               | 21              | 1000   | 1.100 | A2                     |

### Sustainability rating (per m<sup>2</sup>)

Database ecoinvent

OI3<sub>Kon</sub> 42.1

Calculated by HFA

## Details of sustainability rating

### Database ecoinvent

| Lifecycle<br>(Phases) | GWP<br>[kg CO <sub>2</sub> -e.] | AP<br>[kg SO <sub>2</sub> -e.] | EP<br>[kg PO <sub>4</sub> -e.] | ODP<br>[kg R11-e.] | POCP<br>[kg Ethen-e.] |  |
|-----------------------|---------------------------------|--------------------------------|--------------------------------|--------------------|-----------------------|--|
| A1 - A3               |                                 | 0.164                          | 0.074                          | 3,43E-6            | 0.029                 |  |

| Lifecycle<br>(Phases) | PERE<br>[MJ] | PERM<br>[MJ] | PERT<br>[MJ] | PENRE<br>[MJ] | PENRM<br>[MJ] | PENRT<br>[MJ] |
|-----------------------|--------------|--------------|--------------|---------------|---------------|---------------|
| A1 - A3               | 77.224       | 473.735      | 550.959      | 638.874       | 29.215        | 668.089       |