dataholz.eu

gdrtxn04a-04 8/2/23 Holzforschung Austria HFA, SP

Intermediate floor - gdrtxn04a-04

intermediate floor, timber frame construction, directly, dry, with filling, other surface

Performance rating

Fire protection	REI	30	
performance			
with planking 19 mm (without floor constru Classified by HFA	n; maximum span = uction, with ceiling	= 5 m; maximum load E _{d,fi} = 4,5 k _j beam 80/220)	(N∕m²
Germany			
F30			

Load $E_{d,fi}$ according to the German certification document

Corresponding proof: DIN 4102-4:2016-05, Tabelle 10.12, Zeile 1

Thermal performance	U Diffusion	suitable
Acoustic performance	R _w (C;C _{tr}) L _{n,w} (C _l)	58(-6;-13) dB 64(3)
Assessed by Müller-BBM		
Mass per unit area	m	121.50 kg/m ²





Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

	Thickness	Building material Thermal performance					Reaction to fire
			λ	µ min – max	ρ	с	EN
А	25.0	dry screed	0.210	8	900	1.050	A1
В	40.0		0.040	1	180	1.030	A1
С	30.0	fill (m' ca. 45 kg/m²)	0.700	1	1800	1.000	A1
D	0.2	trickling protection					E
Е	16.0	OSB	0.130	200	600	1.700	D
F	240.0	construction timber (80/; e=625)	0.120	50	450	1.600	D
G	100.0	Cellulose fibre [040; 50]	0.040	1	50	2.000	E
Н	16.0	spruce wood tongeue and groove planking	0.120	50	450	1.600	D
I	9.5	gypsum plaster board type A	0.250	4 - 10	680	1.050	A2

Sustainability rating (per m²)

Database	ecoinvent	

38.180 OI3_{Kon} 24.4 **Built-in renewable materials** kg Biogenic carbon in kg CO₂-e. kg CO₂ 55.410 Calculated by HFA 665.440 Energy use of Primary Energy MJ Share of renewable PE % 55.30 Calculated by TUM

Database GaBi (ÖKOBAUDAT)

dataholz.eu – Catalogue of timber building materials, components and component connections reviewed to consider thermal, acoustic, fire performance requirements and ecological drivers for timber construction released by accredited testing institutes. These datasheets will generally be accepted as proofs of compliance by building authorities.

dataholz.eu

Designation: Last updated: Source: Editor: gdrtxn04a-04 8/2/23 Holzforschung Austria HFA, SP

Details of sustainability rating

Database ecoinvent

Lifecycle	GWP	AP	EP	ODP	POCP	
(Phases)	[kg CO ₂ -e.]	[kg SO ₂ -e.]	[kg PO ₄ -e.]	[kg R11-e.]	[kg Ethen-e.]	
A1 - A3		0.127	0.046	1,95E-6	0.039	
Lifecycle	PERE	PERM	PERT	PENRE	PENRM	PENRT
(Phases)	[MJ]	[MJ]	[LM]	[M]	[MJ]	[LM]
A1 - A3	114.674	595.354	710.028	374.903	16.350	391.253

Database GaBi (ÖKOBAUDAT)

Lifecycle	GWP	AP	EP	ODP	POCP	
(Phases)	[kg CO ₂ -e.]	[kg SO ₂ -e.]	[kg PO ₄ -e.]	[kg R11-e.]	[kg Ethen-e.]	
A1 - A3		0.107	0.017	9,12E-7	0.020	
C1 - C4		0.012	0.006	8,48E-8	0.001	
A1 - C4		0.120	0.024	1,00E-6	0.022	
Lifecycle	PERE	PERM	PERT	PENRE	PENRM	PENRT
(Phases)	[MJ]	[MJ]	[M]	[MJ]	[MJ]	[M]
A1 - A3	166.662	640.204	808.914	459.960	41.713	501.822
C1 - C4	2.939	-562.097	-559.159	31.000	-6.901	24.099
A1 - C4	169.916	78.366	250.330	495.522	34.853	530.524