

Internal wall - iwrxxo01b-02

internal wall, timber frame construction, without dry lining, other surface

Performance rating

Fire protection performance REI 60

maximum ceiling height = 3 m; maximum load $E_{d,fi}$ = 50,0 kN/m


Classified by MA39

Classified by HFA

Acoustic performance R_w (C ; C_{tr})
 $L_{n,w}$ (C_i)

Mass per unit area m 48.60 kg/m²

Calculation based on GF



Note: The fire resistance is only valid when wall is used as partition with only one side exposed to fire.
 (B=60/100); e=625

Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

	Thickness	Building material	Thermal performance				Reaction to fire	
			λ	μ min – max	ρ	c	EN	
A	25.0	gypsum plaster board type DF (2x12,5 mm) or	0.250	10	800	1.050	A2	
A	25.0	gypsum fibre board (2x12,5 mm)	0.320	21	1000	1.100	A2	
B	100.0	construction timber (60/100 or 60/160; e=*)	0.120	50	450	1.600	D	
C	100.0	mineral wool [035; 50; <1000°C]	0.035	1	50	1.030	A1	
D	25.0	gypsum plaster board type DF (2x12,5 mm) or	0.250	10	800	1.050	A2	
D	25.0	gypsum fibre board (2x12,5 mm)	0.320	21	1000	1.100	A2	

Sustainability rating (per m²)

Database ecoinvent

OI3_{Kon} 27.2

Calculated by HFA

Details of sustainability rating

Database ecoinvent

Lifecycle (Phases)	GWP [kg CO ₂ -e.]	AP [kg SO ₂ -e.]	EP [kg PO ₄ -e.]	ODP [kg R11-e.]	POCP [kg Ethen-e.]	
A1 - A3		0.095	0.044	2,35E-6	0.012	

Lifecycle (Phases)	PERE [MJ]	PERM [MJ]	PERT [MJ]	PENRE [MJ]	PENRM [MJ]	PENRT [MJ]
A1 - A3	31.702	78.614	110.316	376.352	0.000	376.352