

Pitched roof - sdmhzi02a-01

pitched roof, solid wood construction, ventilated, with dry lining, not suspended, other surface

Performance rating

Fire protection performance REI 60

maximum span = 5 m; maximum load $E_{d,fi}$ = 5 kN/m² (without roof structure)
Classified by HFA

Germany

REI60

Load $E_{d,fi}$ according to the German certification document

Corresponding proof: manufacturer-specific



Thermal performance U Diffusion 0.12 W/(m²K)
suitable

Calculated by TUM

Acoustic performance R_w (C ; C_{tr}) 53(-1;-7) dB
 $L_{n,w}$ (C_i)

Assessed by Müller-BBM

Mass per unit area m 176.00 kg/m²



Note: The design of the under-roof construction and of the counter-battens have to be specified according to the roof pitch and the national requirements.

Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

	Thickness	Building material	Thermal performance				Reaction to fire EN
			λ	μ min – max	ρ	c	
A		concrete roof tile /tiled roof			2100		A1
B	30.0	spruce wood battens (30/50)	0.120	50	450	1.600	D
C	30.0	spruce wood counter battens (Germany 30mm); Austria: minimum 50mm	0.120	50	450	1.600	D
D	22.0	softboard [045; 250] - rigid underlay	0.045	5	250	2.100	E
E	200.0	wood-fibre insulation board [0,040; R=200] on-roof insulation	0.040	5 - 7	200	2.100	E
F	0.2	sealing sheet (air tight)					
G	120.0	cross laminated timber	0.130	50	500	1.600	D
H	60.0	spruce wood battens (60/60; e=400)	0.120	50	450	1.600	D
I	60.0	mineral wool [040; 11; <1000°C]	0.040	1	11	1.030	A1
J	12.5	gypsum plaster board type DF	0.250	10	800	1.050	A2

Sustainability rating (per m²)

Databaseecoinvent

Ol3_{kon} 66.0

Calculated by HFA

Database GaBi (ÖKOBAUDAT)

Built-in renewable materials kg 128.750
Biogenic carbon in kg CO₂e. kg CO₂ 183.850
Energy use of Primary Energy MJ 1833.000
Share of renewable PE % 32.33

Calculated by TUM

Details of sustainability rating

Database ecoinvent

Lifecycle (Phases)	GWP [kg CO ₂ -e.]	AP [kg SO ₂ -e.]	EP [kg PO ₄ -e.]	ODP [kg R11-e.]	POCP [kg Ethen-e.]	
A1 - A3		0.305	0.135	6,28E-6	0.072	

Lifecycle (Phases)	PERE [MJ]	PERM [MJ]	PERT [MJ]	PENRE [MJ]	PENRM [MJ]	PENRT [MJ]
A1 - A3	137.302	1639.381	1776.682	1133.047	91.189	1224.235

Database GaBi (ÖKOBAUDAT)

Lifecycle (Phases)	GWP [kg CO ₂ -e.]	AP [kg SO ₂ -e.]	EP [kg PO ₄ -e.]	ODP [kg R11-e.]	POCP [kg Ethen-e.]	
A1 - A3		0.197	0.041	4,64E-6	0.042	
C1 - C4		0.008	0.002	2,12E-7	0.001	
A1 - C4		0.209	0.044	4,86E-6	0.042	

Lifecycle (Phases)	PERE [MJ]	PERM [MJ]	PERT [MJ]	PENRE [MJ]	PENRM [MJ]	PENRT [MJ]
A1 - A3	588.090	1891.109	2476.757	1180.276	70.048	1249.652
C1 - C4	3.427	-1886.892	-1883.465	45.450	-57.374	-11.924
A1 - C4	592.596	4.476	594.630	1240.402	12.726	1252.457