

Pitched roof - sdmhzi02a-03

pitched roof, solid wood construction, ventilated, with dry lining, not suspended, other surface

Performance rating

Fire protection performance REI 60

maximum span = 5 m; maximum load $E_{d,fi}$ = 5 kN/m² (without roof structure)
Classified by HFA

Germany

REI60

Load $E_{d,fi}$ according to the German certification document

Corresponding proof: manufacturer-specific



Thermal performance U Diffusion 0.14 W/(m²K)
suitable

Calculated by TUM

Acoustic performance R_w (C ; C_{tr}) 45(-1;-7) dB
 $L_{n,w}$ (C_i)

Assessed by Müller-BBM

Mass per unit area m 159.40 kg/m²



Note: The design of the under-roof construction and of the counter-battens have to be specified according to the roof pitch and the national requirements.

Underlay laminated on insulation board

Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

	Thickness	Building material	Thermal performance				Reaction to fire EN
			λ	μ min – max	ρ	c	
A		concrete roof tile /tiled roof			2100		A1
B	30.0	spruce wood battens (30/50)	0.120	50	450	1.600	D
C	30.0	spruce wood counter battens (Germany 30mm); Austria: minimum 50mm	0.120	50	450	1.600	D
D		sarking membrane $s_d \leq 0,3m$			1000		E
E	180.0	mineral wool [040; 130] on-roof insulation	0.040	1	130	1.030	
F	0.2	sealing sheet (air tight)					
G	120.0	cross laminated timber	0.130	50	500	1.600	D
H	60.0	spruce wood battens (60/60; e=400)	0.120	50	450	1.600	D
I	60.0	mineral wool [040; 11; <1000°C]	0.040	1	11	1.030	A1
J	12.5	gypsum plaster board type DF	0.250	10	800	1.050	A2

Sustainability rating (per m²)

Databaseecoinvent

Ol3_{Kon} 89.5

Calculated by HFA

Database GaBi (ÖKOBAUDAT)

Built-in renewable materials kg 66.520
Biogenic carbon in kg CO₂-e. kg CO₂ 95.930
Energy use of Primary Energy MJ 1386.830
Share of renewable PE % 23.58

Calculated by TUM

Details of sustainability rating

Database ecoinvent

Lifecycle (Phases)	GWP [kg CO ₂ -e.]	AP [kg SO ₂ -e.]	EP [kg PO ₄ -e.]	ODP [kg R11-e.]	POCP [kg Ethen-e.]	
A1 - A3		0.425	0.141	5,10E-6	0.161	

Lifecycle (Phases)	PERE [MJ]	PERM [MJ]	PERT [MJ]	PENRE [MJ]	PENRM [MJ]	PENRT [MJ]
A1 - A3	79.108	958.764	1037.872	1066.432	33.300	1099.732

Database GaBi (ÖKOBAUDAT)

Lifecycle (Phases)	GWP [kg CO ₂ -e.]	AP [kg SO ₂ -e.]	EP [kg PO ₄ -e.]	ODP [kg R11-e.]	POCP [kg Ethen-e.]	
A1 - A3		0.302	0.046	4,13E-6	0.030	
C1 - C4		0.010	0.009	1,91E-7	0.002	
A1 - C4		0.316	0.056	4,33E-6	0.031	

Lifecycle (Phases)	PERE [MJ]	PERM [MJ]	PERT [MJ]	PENRE [MJ]	PENRM [MJ]	PENRT [MJ]
A1 - A3	323.589	1139.008	1459.714	1008.820	51.363	1059.513
C1 - C4	2.386	-1129.448	-1127.061	35.231	0.000	35.231
A1 - C4	327.061	9.819	333.998	1059.771	51.415	1110.516