

Designation: sdrhzi02a-04
Last updated: 8/2/23

Source: Holzforschung Austria

Editor: HFA, SP

Pitched roof - sdrhzi02a-04

pitched roof, timber frame construction, ventilated, with dry lining, not suspended, other surface

Performance rating

Fire protection REI 30 performance

maximum span = 5 m; maximum load $E_{d,fi}$ = 3,66 kN/m²

Classified by HFA

Thermal performance U 0.21 W/(m²K) Suitable


Calculated by HFA


Acoustic performance R_w (C;C_{tr}) 50(-2;-8) dB

L_{n,w} (C_t)

with a tiled roof Rw = 49 dB Assessed by TGM

Calculation based on gypsum plaster board type DF





Note: The design of the under-roof construction and of the counterbattens have to be specified according to the roof pitch and the national requirements.

Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

	Thickness	Building material	Thermal performance				Reaction to fire	
			λ	μ min – max	ρ	С	EN	
Α		concrete roof tile or tiled roof			2100		A1	
В	30.0	spruce wood battens (30/50)	0.120	50	450	1.600	D	
С	50.0	spruce wood counter battens (minimum height 50 mm)	0.120	50	450	1.600	D	
D		sarking membrane sd ≤ 0,3 m			1000		Е	
Ε	24.0	spruce wood closed cladding without spacing of cladding boards	0.120	50	450	1.600	D	
F	200.0	construction timber (80/; e=800)	0.120	50	450	1.600	D	
G	200.0	mineral wool [038; ≥33; ≥1000°C]	0.038	1	33	1.030	A1	
Н		vapour barrier sd≥ 6m			1000			
Ι	24.0	spruce wood cladding with spacing of cladding boards(24/100); a=400	0.120	50	450	1.600	D	
J	12.5	gypsum plaster board type DF or	0.250	10	800	1.050	A2	
J	12.5	gypsum fibre board	0.320	21	1000	1.100	A2	

Sustainability rating (per m²)

Database ecoinvent

Ol3_{Kon} 29.0

Calculated by HFA



Designation: sdrhzi02a-04 8/2/23 Holzforschung Austria Last updated:

Source:

Editor: HFA, SP

Details of sustainability rating

Database ecoinvent

Lifecycle	GWP	AP	EP	ODP	POCP	
(Phases)	[kg CO ₂ -e.]	[kg SO ₂ -e.]	[kg PO ₄ -e.]	[kg R11-e.]	[kg Ethen-e.]	
A1 - A3		0.141	0.049	2.14E-6	0.053	
Lifecycle	PERE	PERM	PERT	PENRE	PENRM	PENRT
Lifetytie	I LILL	I LIMI	I LIVI	I LIVING	FEININI	I LIVIVI
(Phases)	[MJ]	[W1]	[MJ]	[MJ]	[MJ]	[MJ]