

Designation: sdrhzi02b-01 Last updated: 8/2/23

Holzforschung Austria Source:

Editor: HFA, SP

Pitched roof - sdrhzi02b-01

pitched roof, timber frame construction, ventilated, with dry lining, not suspended, other surface

Performance rating

Fire protection

performance maximum span = 5 m; maximum load $E_{d,fi}$ = 3,66 kN/m² Classified by HFA Thermal performance U $0.19 \text{ W/(m}^2\text{K)}$ Diffusion suitable Calculated by HFA Acoustic performance R_w (C;C_{tr}) 51(-2;-8) dB


60


with a tiled roof Rw = 49 (-2; -8) dBAssessed by TGM

Mass per unit area 49.70 kg/m^2

 $L_{n,w}$ (C_I)

Calculation based on gypsum plaster board type DF





Note: The design of the under-roof construction and of the counterbattens have to be specified according to the roof pitch and the national requirements.

Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

| | Thickness | Building material | Thermal performance | | | | Reaction to fire | |
|---|-----------|---|---------------------|-------------|------|-------|------------------|--|
| | | | λ | μ min – max | ρ | С | EN | |
| Α | | concrete roof tile or tiled roof | | | 2100 | | A1 | |
| В | 30.0 | spruce wood battens (30/50) | 0.120 | 50 | 450 | 1.600 | D | |
| С | 50.0 | spruce wood counter battens (minimum height 50 mm) | 0.120 | 50 | 450 | 1.600 | D | |
| D | | sarking membrane sd ≤ 0,3m | | | 1000 | | E | |
| E | 24.0 | spruce wood closed cladding without spacing of cladding boards | 0.120 | 50 | 450 | 1.600 | D | |
| F | 220.0 | construction timber (80/; e=800) | 0.120 | 50 | 450 | 1.600 | D | |
| G | 220.0 | mineral wool [040; ≥16; <1000°C] | 0.040 | 1 | 16 | 1.030 | A1 | |
| Н | | vapour barrier sd≥ 6m | | | 1000 | | | |
| I | 24.0 | spruce wood cladding with spacing of cladding boards(24/100); a=400 | 0.120 | 50 | 450 | 1.600 | D | |
| J | 25.0 | gypsum plaster board type DF (2x12,5 mm) or | 0.250 | 10 | 800 | 1.050 | A2 | |
| J | 25.0 | gypsum fibre board (2x12,5 mm) | 0.320 | 21 | 1000 | 1.100 | A2 | |

Sustainability rating (per m²)

| Database ecoinvent | | | | | | | |
|--------------------|------|--|--|--|--|--|--|
| Ol3 _{Kon} | 26.8 | | | | | | |
| Calculated by HFA | | | | | | | |



Designation: sdrhzi02b-01 Last updated:

8/2/23 Holzforschung Austria Source:

Editor: HFA, SP

Details of sustainability rating

Database ecoinvent

| Lifecycle | GWP | AP | EP | ODP | POCP | |
|-----------|--------------------------|--------------------------|--------------------------|-------------|---------------|-------|
| (Phases) | [kg CO ₂ -e.] | [kg SO ₂ -e.] | [kg PO ₄ -e.] | [kg R11-e.] | [kg Ethen-e.] | |
| A1 - A3 | | 0.116 | 0.055 | 2,85E-6 | 0.024 | |
| | | | | | | |
| Lifecycle | PERE | PERM | PERT | PENRE | PENRM | PENRT |
| (Phases) | [MJ] | [MJ] | [MJ] | [MJ] | [MJ] | [MJ] |
| | | | | | | |