

Designation: sdrhzi02b-06 Last updated: 8/2/23

Holzforschung Austria Source:

Editor: HFA, SP

Pitched roof - sdrhzi02b-06

pitched roof, timber frame construction, ventilated, with dry lining, not suspended, other surface

Performance rating

Fire protection

Assessed by TGM


performance maximum span = 5 m; maximum load $E_{d,fi}$ = 3,66 kN/m² Classified by HFA Thermal performance U $0.23 \text{ W/(m}^2\text{K)}$ Diffusion suitable Calculated by HFA Acoustic performance R_w (C;C_{tr}) 51(-4;-10) dB


60

 $L_{n,w}$ (C_l) with a tiled roof Rw = 49 (-4; -10) dB

Mass per unit area

Calculation based on gypsum plaster board type DF





Note: The design of the under-roof construction and of the counterbattens have to be specified according to the roof pitch and the national requirements.

Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

 48.40 kg/m^2

	Thickness	Building material	Thermal performance				Reaction to fire	
			λ	μ min – max	ρ	С	EN	
Α		concrete roof tile or tiled roof			2100		A1	
В	30.0	spruce wood battens (30/50)	0.120	50	450	1.600	D	
С	50.0	spruce wood counter battens (minimum height 50 mm)	0.120	50	450	1.600	D	
D		sarking membrane sd ≤ 0,3 m			1000		E	
E	24.0	spruce wood closed cladding without spacing of cladding boards	0.120	50	450	1.600	D	
F	200.0	construction timber (80/; e=800)	0.120	50	450	1.600	D	
G	200.0	sheep wool [0,041; R=26]	0.041	1	30	1.720	E	
Н		vapour barrier sd≥ 6m			1000			
l	24.0	spruce wood cladding with spacing of cladding boards(24/100); a=400	0.120	50	450	1.600	D	
J	25.0	gypsum plaster board type DF (2x12,5 mm) or	0.250	10	800	1.050	A2	
J	25.0	gypsum fibre board (2x12,5 mm)	0.320	21	1000	1.100	A2	

Sustainability rating (per m²)

Database ecoinvent						
OI3 _{Kon}	19.5					
Calculated by HFA						



Designation: sdrhzi02b-06 8/2/23 Holzforschung Austria Last updated:

Source:

HFA, SP Editor:

Details of sustainability rating

Database ecoinvent

Lifecycle	GWP	AP	EP	ODP	POCP	
(Phases)	[kg CO ₂ -e.]	[kg SO ₂ -e.]	[kg PO ₄ -e.]	[kg R11-e.]	[kg Ethen-e.]	
A1 - A3		0.081	0.038	2,61E-6	0.021	
Lifecycle	PERE	PERM	PERT	PENRE	PENRM	PENRT
(Phases)	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]
A1 - A3	88.833	603.065	691.898	368.807	11.942	380.750