

Designation: sdrhzi06a-06 8/2/23 Last updated:

Holzforschung Austria Source:

Editor: HFA, SP

## Pitched roof - sdrhzi06a-06

pitched roof, timber frame construction, ventilated, with dry lining, not suspended, other surface


### Performance rating


Fire protection performance maximum span = 5 m; maximum load  $E_{d,fi}$  = 2,62 kN/m<sup>2</sup> Classified by HFA

Thermal performance	U Diffusion	0.18 W/(m <sup>2</sup> K) suitable
Calculated by HFA		
Acoustic performance	R <sub>w</sub> (C;C <sub>tr</sub> ) L <sub>n,w</sub> (C <sub>l</sub> )	53(-3;-9) dB

Mass per unit area  $59.10~kg/m^2$ 

Calculation based on gypsum plaster board type DF





Note: The design of the under-roof construction and of the counterbattens have to be specified according to the roof pitch and the national requirements.

### Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

	Thickness	Building material	Thermal per	formance			Reaction to fire
			λ	μ min – max	ρ	С	EN
Α		concrete roof tile or tiled roof			2100		A1
В	30.0	spruce wood battens (30/50)	0.120	50	450	1.600	D
С	50.0	spruce wood counter battens (minimum height 50 mm)	0.120	50	450	1.600	D
D		sarking membrane sd ≤ 0,3 m			1000		Е
E	24.0	planking spruce wood closed cladding without spacing of cladding boards	0.120	50	450	1.600	D
F	200.0	construction timber (80/; e=800)	0.120	50	450	1.600	D
G	200.0	cellulose fibre [0,040; R=55]	0.040	1 - 2	55	2.000	В
Н	15.0	OSB (sealed with airtight tape)	0.130	200	600	1.700	D
1	50.0	spruce wood cross battens (50/80;a=400)	0.120	50	450	1.600	D
J	50.0	cellulose fibre [0,040; R=55]	0.040	1 - 2	55	2.000	В
K	12.5	gypsum plaster board type DF or	0.250	10	800	1.050	A2
K	12.5	gypsum fibre board	0.320	21	1000	1.100	A2

# Sustainability rating (per m²)

Database ecoinvent OI3<sub>Kon</sub> 20.4 Calculated by HFA



Designation: sdrhzi06a-06 8/2/23 Holzforschung Austria Last updated:

Source:

HFA, SP Editor:

### Details of sustainability rating

#### Database ecoinvent

Lifecycle	GWP	AP	EP	ODP	POCP	
(Phases)	[kg CO <sub>2</sub> -e.]	[kg SO <sub>2</sub> -e.]	[kg PO <sub>4</sub> -e.]	[kg R11-e.]	[kg Ethen-e.]	
A1 - A3		0.116	0.051	2,48E-6	0.025	
Lifecycle	PERE	PERM	PERT	PENRE	PENRM	PENRT
(Phases)	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]
A1 - A3	129.648	795.188	924.836	375.244	17.244	392.488