

Designation: sdrhzi07b-00 Last updated: 8/2/23

Source: Holzforschung Austria

Editor: HFA, SP

# Pitched roof - sdrhzi07b-00

pitched roof, timber frame construction, ventilated, with dry lining, not suspended, other surface

#### Performance rating

Fire protection

 $\begin{array}{c} \textbf{performance} \\ \textbf{maximum span} = 5 \text{ m; maximum load } E_{d,fi} = 3,66 \text{ kN/m}^2 \\ \textbf{Classified by HFA} \\ \hline \\ \textbf{Thermal performance} & \textbf{U} & 0.21 \text{ W/(m}^2 \text{K)} \\ \textbf{Diffusion} & \text{suitable} \\ \hline \\ \textbf{Calculated by HFA} \\ \hline \\ \textbf{Acoustic performance} & \textbf{R}_{\textbf{w}} \textbf{(C;C}_{\textbf{tr}} \textbf{)} & 53(-2; -8) \text{ dB} \\ \hline \end{array}$ 


60


with a tiled roof Rw = 51 (-2; -8) dB Assessed by TGM

 $\begin{tabular}{lll} \begin{tabular}{lll} \begin{$ 

 $L_{n,w}$  (C<sub>I</sub>)

Calculation based on gypsum plaster board type DF





Note: The design of the under-roof construction and of the counterbattens have to be specified according to the roof pitch and the national requirements.

### Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

	Thickness	Building material	Thermal performance				Reaction to fire
			λ	μ min – max	ρ	С	EN
Α		concrete roof tile or tiled roof			2100		A1
В	30.0	spruce wood battens (30/50)	0.120	50	450	1.600	D
С	50.0	spruce wood counter battens (minimum height 50 mm)	0.120	50	450	1.600	D
D		sarking membrane sd ≤ 0,3 m			1000		E
	12.0	OSB	0.130	200	600	1.700	D
=	200.0	construction timber (80/; e=800)	0.120	50	450	1.600	D
Ĵ	200.0	mineral wool [040; ≥16; <1000°C]	0.040	1	16	1.030	A1
1	15.0	OSB	0.130	200	600	1.700	D
		vapour barrier sd≥ 11m			1000		
	24.0	spruce wood cladding with spacing of cladding boards(24/100); a=400	0.120	50	450	1.600	D
(	25.0	gypsum plaster board type DF (2x12,5 mm) or	0.250	10	800	1.050	A2
(	25.0	gypsum fibre board (2x12,5 mm)	0.320	21	1000	1.100	A2

### Sustainability rating (per m<sup>2</sup>)

Database ecoinvent

OI3<sub>Kon</sub> 32.0

Calculated by HFA



Designation: sdrhzi07b-00 8/2/23 Holzforschung Austria Last updated:

Source:

HFA, SP Editor:

## Details of sustainability rating

#### Database ecoinvent

Lifecycle	GWP	AP	EP	ODP	POCP	
(Phases)	[kg CO <sub>2</sub> -e.]	[kg SO <sub>2</sub> -e.]	[kg PO <sub>4</sub> -e.]	[kg R11-e.]	[kg Ethen-e.]	
A1 - A3		0.133	0.060	3,15E-6	0.025	
Lifecycle	PERE	PERM	PERT	PENRE	PENRM	PENRT
(Phases)	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]
A1 - A3	112.776	549.930	662.706	502.676	30.376	533.052