

Designation: sdrhzi07b-05 Last updated: 8/2/23

Holzforschung Austria Source:

Editor: HFA, SP

# Pitched roof - sdrhzi07b-05

pitched roof, timber frame construction, ventilated, with dry lining, not suspended, other surface

## Performance rating

Fire protection


performance maximum span = 5 m; maximum load  $E_{d,fi}$  = 3,66 kN/m<sup>2</sup> Classified by HFA Thermal performance U  $0.21 \text{ W/(m}^2\text{K)}$ Diffusion suitable Calculated by HFA Acoustic performance  $R_w$  (C;C<sub>tr</sub>) 54(-2;-8) dB  $L_{n,w}$  (C<sub>I</sub>)

60

with a tiled roof Rw = 52 (-2; -8) dBAssessed by TGM

Mass per unit area  $61.00 \text{ kg/m}^2$ 

Calculation based on gypsum plaster board type DF



Note: The design of the under-roof construction and of the counterbattens have to be specified according to the roof pitch and the national requirements.

### Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

	Thickness	Building material	Thermal performance				Reaction to fire	
			λ	μ min – max	ρ	С	EN	
Α		concrete roof tile or tiled roof			2100		A1	
В	30.0	spruce wood battens (30/50)	0.120	50	450	1.600	D	
С	50.0	spruce wood counter battens (minimum height 50 mm)	0.120	50	450	1.600	D	
D		sarking membrane sd ≤ 0,3 m			1000		Е	
Е	12.0	OSB	0.130	200	600	1.700	D	
F	200.0	construction timber (80/; e=800)	0.120	50	450	1.600	D	
G	200.0	cellulose fibre [0,040; R=55]	0.040	1 - 2	55	2.000	В	
Н	15.0	OSB	0.130	200	600	1.700	D	
1		vapour barrier sd≥ 11m			1000			
J	24.0	spruce wood cladding with spacing of cladding boards(24/100); a=400	0.120	50	450	1.600	D	
K	25.0	gypsum plaster board type DF (2x12,5 mm) or	0.250	10	800	1.050	A2	
K	25.0	gypsum fibre board (2x12,5 mm)	0.320	21	1000	1.100	A2	

### Sustainability rating (per m<sup>2</sup>)

Database ecoinvent OI3<sub>Kon</sub> 25.2

Calculated by HFA



Designation: sdrhzi07b-05 8/2/23 Holzforschung Austria Last updated:

Source:

Editor: HFA, SP

### Details of sustainability rating

#### Database ecoinvent

Lifecycle	GWP	AP	EP	ODP	POCP	
(Phases)	[kg CO <sub>2</sub> -e.]	[kg SO <sub>2</sub> -e.]	[kg PO <sub>4</sub> -e.]	[kg R11-e.]	[kg Ethen-e.]	
A1 - A3		0.117	0.051	2,73E-6	0.022	
Lifecycle	PERE	PERM	PERT	PENRE	PENRM	PENRT
(Phases)	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]