

Designation: sdrhzi08a-05 Last updated: 8/2/23

Holzforschung Austria Source:

Editor: HFA, SP

Pitched roof - sdrhzi08a-05

pitched roof, timber frame construction, ventilated, with dry lining, not suspended, other surface

Performance rating

30 Fire protection performance


maximum span = 5 m; maximum load $E_{d,fi}$ = 3,66 kN/m²


Classified by HFA

Thermal performance U $0.18 \text{ W/(m}^2\text{K)}$ Diffusion suitable Calculated by HFA Acoustic performance R_w (C;C_{tr}) 52(-2;-8) dB $L_{n,w}$ (C_I) with a tiled roof Rw = 50 (-2; -8) dBAssessed by TGM

Mass per unit area 41.40 kg/m^2

Calculation based on gypsum plaster board type DF





Note: The design of the under-roof construction and of the counterbattens have to be specified according to the roof pitch and the national requirements.

Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

	Thickness	Building material	Thermal per	Thermal performance			
			λ	μ min – max	ρ	С	EN
Α		concrete roof tile or tiled roof			2100		A1
В	30.0	spruce wood battens (30/50)	0.120	50	450	1.600	D
С	50.0	spruce wood counter battens (minimum height 50 mm)	0.120	50	450	1.600	D
D	15.0	fibreboard (MDF)	0.140	11	600	1.700	D
E	200.0	construction timber (80/; e=800)	0.120	50	450	1.600	D
F	200.0	mineral wool [038; ≥33; ≥1000°C]	0.038	1	33	1.030	A1
G		vapour barrier sd≥ 1 m			1000		
Н	50.0	spruce wood cross battens (50/80;a=400)	0.120	50	450	1.600	D
ı	50.0	mineral wool [038; ≥33; ≥1000°C]	0.038	1	33	1.030	A1
J	12.5	gypsum plaster board type DF or	0.250	10	800	1.050	A2
J	12.5	gypsum fibre board	0.320	21	1000	1.100	A2

$\textbf{Sustainability rating} \ (\text{per m}^2)$

Database ecoinvent

OI3_{Kon} 37.9

Calculated by HFA



Designation: sdrhzi08a-05 Last updated:

8/2/23 Holzforschung Austria Source:

Editor: HFA, SP

Details of sustainability rating

Database ecoinvent

Lifecycle	GWP	AP	EP	ODP	POCP	
(Phases)	[kg CO ₂ -e.]	[kg SO ₂ -e.]	[kg PO ₄ -e.]	[kg R11-e.]	[kg Ethen-e.]	
A1 - A3		0.169	0.056	2,21E-6	0.060	
Lifecycle	PERE	PERM	PERT	PENRE	PENRM	PENRT
(Phases)	[MJ]	[M1]	[MJ]	[MJ]	[MJ]	[MJ]
A1 - A3	78.253	475.925	554.178	462.304	46.624	508.928