

Designation: sdrhzi08b-00 Last updated: 8/2/23

Source: Holzforschung Austria

Editor: HFA, SP

Pitched roof - sdrhzi08b-00


pitched roof, timber frame construction, ventilated, with dry lining, not suspended, other surface


Performance rating

Fire protection REI 60 performance maximum span = 5 m; maximum load $E_{d,fi} = 3,66 \text{ kN/m}^2$ Classified by HFA

Thermal performance	U Diffusion	0.18 W/(m ² K) suitable
Calculated by HFA		
Acoustic performance	R _w (C;C _{tr}) L _{n,w} (C _I)	53(-3;-9) dB
with a tiled roof Rw = 51 Assessed by TGM	(-3; -9) dB	

Calculation based on gypsum plaster board type DF





Note: The design of the under-roof construction and of the counterbattens have to be specified according to the roof pitch and the national requirements.

Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

	Thickness	Building material	Thermal per	Thermal performance			
			λ	μ min – max	ρ	С	EN
Α		concrete roof tile or tiled roof			2100		A1
В	30.0	spruce wood battens (30/50)	0.120	50	450	1.600	D
С	50.0	spruce wood counter battens (minimum height 50 mm)	0.120	50	450	1.600	D
D	15.0	fibreboard (MDF)	0.140	11	600	1.700	D
E	200.0	construction timber (80/; e=800)	0.120	50	450	1.600	D
F	200.0	mineral wool [040; ≥16; <1000°C]	0.040	1	16	1.030	A1
G		vapour barrier sd≥ 1 m			1000		
Н	50.0	spruce wood cross battens (50/80;a=400)	0.120	50	450	1.600	D
1	50.0	mineral wool [040; ≥16; <1000°C]	0.040	1	16	1.030	A1
J	25.0	gypsum plaster board type DF (2x12,5 mm) or	0.250	10	800	1.050	A2
J	25.0	gypsum fibre board (2x12,5 mm)	0.320	21	1000	1.100	A2

Sustainability rating (per m²)

Database ecoinvent

OI3_{Kon}
Calculated by HFA

33.1



Designation: sdrhzi08b-00 8/2/23 Holzforschung Austria Last updated:

Source:

HFA, SP Editor:

Details of sustainability rating

Database ecoinvent

Lifecycle	GWP	AP	EP	ODP	POCP	
(Phases)	[kg CO ₂ -e.]	[kg SO ₂ -e.]	[kg PO ₄ -e.]	[kg R11-e.]	[kg Ethen-e.]	
A1 - A3		0.130	0.058	2,90E-6	0.023	
Lifecycle	PERE	PERM	PERT	PENRE	PENRM	PENRT
(Phases)	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]
A1 - A3	81.718	475.925	557.643	493.904	46.624	540.528