

Designation: sdrhzo02a-05 Last updated: 8/2/23

Source: Holzforschung Austria

Editor: HFA, SP

Pitched roof - sdrhzo02a-05

pitched roof, timber frame construction, ventilated, without dry lining, directly, other surface

Performance rating

Fire protection REI 30 performance maximum span = 5 m; maximum load $E_{d.fi} = 2,62 \text{ kN/m}^2$

maximum span = 5 m; maximum load $E_{d,fi}$ = 2,62 kN/m² Classified by HFA

Classified by HFA


Thermal performance U 0.22 W/(m^2 K) suitable Calculated by HFA

Acoustic performance R_w (C;C_{tr}) $L_{n,w}$ (C_i) $L_{n,w}$ (C_i)

with a tiled roof Rw = 50 dB Assessed by TGM

 $\begin{tabular}{lll} \begin{tabular}{lll} \begin{$

Calculation based on gypsum plaster board type DF



Note: The design of the under-roof construction and of the counterbattens have to be specified according to the roof pitch and the national requirements.

Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

Thickness	Building material	Thermal per	Thermal performance				
		λ	μ min – max	ρ	С	EN	
	concrete roof tile or tiled roof			2100		A1	
30.0	spruce wood battens (30/50)	0.120	50	450	1.600	D	
50.0	spruce wood counter battens (minimum height 50 mm)	0.120	50	450	1.600	D	
	sarking membrane sd ≤ 0,3m			1000		E	
12.0	OSB	0.130	200	600	1.700	D	
200.0	construction timber (80/; e=800)	0.120	50	450	1.600	D	
200.0	cellulose fibre [040; E]	0.040	1 - 2	55	2.000	E	
	vapour barrier sd≥ 11 m			1000			
15.0	OSB	0.130	200	600	1.700	D	
12.5	gypsum plaster board type DF or	0.250	10	800	1.050	A2	
12.5	gypsum fibre board	0.320	21	1000	1.100	A2	

Sustainability rating (per m²)

Database ecoinvent

Ol3_{Kon} 22.5

Calculated by HFA



Designation: sdrhzo02a-05 8/2/23 Holzforschung Austria Last updated:

Source:

HFA, SP Editor:

Details of sustainability rating

Database ecoinvent

Lifecycle	GWP	AP	EP	ODP	POCP	
(Phases)	[kg CO ₂ -e.]	[kg SO ₂ -e.]	[kg PO ₄ -e.]	[kg R11-e.]	[kg Ethen-e.]	
A1 - A3		0.108	0.047	2,42E-6	0.020	
Lifecycle	PERE	PERM	PERT	PENRE	PENRM	PENRT
(Phases)	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]	[MJ]