



Pitched roof - sdshzi01a-02

pitched roof, timber frame construction, ventilated, with dry lining, suspended, other surface

Performance rating

Fire protection performance	REI	60
Classified by HFA		
Thermal performance	U Diffusion	0.09 W/(m ² K) suitable
Calculated by HFA		
Acoustic performance	R _w (C _r ;C _{tr}) L _{n,w} (C _i)	44 dB
Assessed by HFA		
Mass per unit area	m	74.10 kg/m ²
Calculation based on gypsum plaster board type DF		



Note: The design of the under-roof construction and of the counter-battens have to be specified according to the roof pitch and the national requirements.

Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

	Thickness	Building material	Thermal performance				Reaction to fire EN
			λ	μ min – max	ρ	c	
A		concrete roof tile			2100		A1
B	30.0	spruce wood	0.120	50	450	1.600	D
C	50.0	spruce wood	0.120	50	450	1.600	D
D		sarking membrane sd ≤ 0,3m			1000		E
E	20.0	softboard [045; 250] - rigid underlay	0.045	5	250	2.100	E
F	400.0	Light composite wood-based beams (I-beams) with solid wood flanges (60/45) and hard board intermediate web (≥ 6,7)	0.400	20 - 30	800	1.700	D
G	400.0	mineral wool [034; 18; <1000°C]	0.034	1	18	1.030	A1
H	15.0	OSB	0.130	200	600	1.700	D
I	27.0	metal rail					
J	13.0	gypsum plaster board type DF	0.250	10	800	1.050	A2
J	13.0	gypsum fibre board	0.320	21	1000	1.100	A2

Sustainability rating (per m²)

Database ecoinvent

013_{Kon} 51.4

Calculated by HFA

Details of sustainability rating

Database ecoinvent

Lifecycle (Phases)	GWP [kg CO ₂ -e.]	AP [kg SO ₂ -e.]	EP [kg PO ₄ -e.]	ODP [kg R11-e.]	POCP [kg Ethen-e.]	
A1 - A3		0.197	0.093	4,16E-6	0.028	

Lifecycle (Phases)	PERE [MJ]	PERM [MJ]	PERT [MJ]	PENRE [MJ]	PENRM [MJ]	PENRT [MJ]
A1 - A3	83.440	393.885	477.325	700.072	26.196	726.267