# dataholz.eu

twrxxo03a-00 8/2/23 Holzforschung Austria HFA, SP

А

B C D E F G

H I

## Compartment wall - twrxxo03a-00

compartment wall, timber frame construction, without dry lining, double-layer, other surface

### Performance rating

| Fire protection performance   | REI   | 45                                    |  |
|---|---|---------------------------------------|--|
| apply to each of the load<br>height = 3 m; maximum l<br>Classified by HFA | baring walls; the whole wa<br>oad E <sub>d,fi</sub> = 19,2 kN∕m           | II: EI90; maximum ceiling             |  |
| Thermal performance   | U<br>Diffusion  | 0.19 W∕(m <sup>2</sup> K)<br>suitable |  |
| Calculated by HFA   |   |                                       |  |
| Acoustic performance  | R <sub>w</sub> (C;C <sub>tr</sub> )<br>L <sub>n,w</sub> (C <sub>l</sub> ) | 58(-3;-11) dB                         |  |
| Assessed by MA39  |   |                                       |  |
| Mass per unit area  | m   | 72.80 kg/m <sup>2</sup>               |  |
| Calculation based on gyp  | sum plaster board type DF   |                                       |  |

Note: e=625

### Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

|   | Thickness | Building material                           | Thermal per | formance    |      |       | Reaction to fire |
|---|-----------|---|-------------|-------------|------|-------|------------------|
|   |           |   | λ           | µ min – max | ρ    | с     | EN               |
| A | 12.5      | gypsum plaster board type DF or             | 0.250       | 10          | 800  | 1.050 | A2               |
| A | 12.5      | gypsum fibre board                          | 0.320       | 21          | 1000 | 1.100 | A2               |
| В | 100.0     | construction timber (60/100; e=*)           | 0.120       | 50          | 450  | 1.600 | D                |
| С | 100.0     | mineral wool [040; ≥16; <1000 °C]           | 0.040       | 1           | 16   | 1.030 | A1               |
| D | 25.0      | gypsum plaster board type DF (2x12,5 mm) or | 0.250       | 10          | 800  | 1.050 | A2               |
| D | 25.0      | gypsum fibre board (2x12,5 mm)              | 0.320       | 21          | 1000 | 1.100 | A2               |
| E | 20.0      | mineral wool [040; ≥16; <1000 °C]           | 0.040       | 1           | 16   | 1.030 | A1               |
| F | 25.0      | gypsum plaster board type DF (2x12,5 mm) or | 0.250       | 10          | 800  | 1.050 | A2               |
| F | 25.0      | gypsum fibre board (2x12,5 mm)              | 0.320       | 21          | 1000 | 1.100 | A2               |
| G | 100.0     | construction timber (60/100; e=*)           | 0.120       | 50          | 450  | 1.600 | D                |
| Н | 100.0     | mineral wool [040; ≥16; <1000 °C]           | 0.040       | 1           | 16   | 1.030 | A1               |
| I | 12.5      | gypsum plaster board type DF or             | 0.250       | 10          | 800  | 1.050 | A2               |
|   | 12.5      | gypsum fibre board                          | 0.320       | 21          | 1000 | 1.100 | A2               |

## Sustainability rating (per m<sup>2</sup>)

#### Database ecoinvent

OI3<sub>Kon</sub>

Calculated by HFA

28.3

# dataholz.eu

Designation: Last updated: Source: Editor: twrxxo03a-00 8/2/23 Holzforschung Austria HFA, SP

#### Details of sustainability rating

#### Database ecoinvent

| Lifecycle | GWP                      | AP                       | EP                       | ODP         | POCP          |       |
|-----------|--------------------------|--------------------------|--------------------------|-------------|---------------|-------|
| (Phases)  | [kg CO <sub>2</sub> -e.] | [kg SO <sub>2</sub> -e.] | [kg PO <sub>4</sub> -e.] | [kg R11-e.] | [kg Ethen-e.] |       |
| A1 - A3   |                          | 0.097                    | 0.045                    | 2,73E-6     | 0.014         |       |
|           |                          |                          |                          |             |               |       |
| Lifecycle | PERE                     | PERM                     | PERT                     | PENRE       | PENRM         | PENRT |
|           |                          |                          |                          |             |               |       |
| (Phases)  | [LM]                     | [MJ]                     | [MJ]                     | [MJ]        | [MJ]          | [MJ]  |

dataholz.eu – Catalogue of timber building materials, components and component connections reviewed to consider thermal, acoustic, fire performance requirements and ecological drivers for timber construction released by accredited testing institutes. These datasheets will generally be accepted as proofs of compliance by building authorities.