

Designation: twrxxo07a-05 Last updated: 8/2/23

Holzforschung Austria Source:

Editor: HFA, SP

Compartment wall - twrxxo07a-05

compartment wall, timber frame construction, without dry lining, double-layer, other surface


Performance rating

Fire protection REI 60 performance apply to each individual load-bearing wall; the whole wall: E190; maximum ceiling height = 3 m; maximum load $E_{d.fi}$ = 19,2 kN/m

Classified by MA39

Classified by HFA Thermal performance U $0.19 \text{ W/(m}^2\text{K)}$ Diffusion suitable Calculated by HFA Acoustic performance R_w (C;C_{tr}) 59(-3;-10) dB $L_{n,w}$ (C_l) Assessed by MA39 Mass per unit area 97.00 kg/m^2

Calculation based on gypsum plaster board type DF



Note: e=400

Register of building materials used for this application, cross-section (from outside to inside, dimensions in mm)

	Thickness	Building material	Thermal per	formance			Reaction to fire
			λ	μ min – max	ρ	С	EN
Α	12.5	gypsum plaster board type DF or	0.250	10	800	1.050	A2
Α	12.5	gypsum fibre board	0.320	21	1000	1.100	A2
В	15.0	OSB	0.130	200	600	1.700	D
С	100.0	construction timber (60/100; e=*)	0.120	50	450	1.600	D
D	100.0	mineral wool [040; ≥16; <1000°C]	0.040	1	16	1.030	A1
Е	15.0	OSB	0.130	200	600	1.700	D
F	12.5	gypsum plaster board type DF or	0.250	10	800	1.050	A2
F	12.5	gypsum fibre board	0.320	21	1000	1.100	A2
G	20.0	mineral wool [040; ≥16; <1000°C]	0.040	1	16	1.030	A1
Н	12.5	gypsum plaster board type DF or	0.250	10	800	1.050	A2
Н	12.5	gypsum fibre board	0.320	21	1000	1.100	A2
I	15.0	OSB	0.130	200	600	1.700	D
J	100.0	construction timber (60/100; e=*)	0.120	50	450	1.600	D
K	100.0	mineral wool [040; ≥16; <1000°C]	0.040	1	16	1.030	A1
L	15.0	OSB	0.130	200	600	1.700	D
М	12.5	gypsum plaster board type DF or	0.250	10	800	1.050	A2
М	12.5	gypsum fibre board	0.320	21	1000	1.100	A2

Sustainability rating (per m²)

Database ecoinvent OI3_{Kon} 36.8 Calculated by HFA



Designation: twrxxo07a-05 Last updated:

8/2/23 Holzforschung Austria Source:

Editor: HFA, SP

Details of sustainability rating

Database ecoinvent

Lifecycle	GWP	AP	EP	ODP	POCP	
(Phases)	[kg CO ₂ -e.]	[kg SO ₂ -e.]	[kg PO ₄ -e.]	[kg R11-e.]	[kg Ethen-e.]	
A1 - A3		0.166	0.071	3,51E-6	0.032	
Lifecycle	PERE	PERM	PERT	PENRE	PENRM	PENRT
Lifecycle (Phases)	PERE [MJ]	PERM [MJ]	PERT [MJ]	PENRE [MJ]	PENRM [MJ]	PENRT [MJ]